

View Online at <https://aerobasegroup.com/nsn/2805-00-691-9640>

Head Style:

Flat

Overall Height:

Between 5.935 inches and 5.940 inches

Diameter:

4.875 inches

Oil Passage Type:

Hole and slot

Pinhole Diameter:

Between 1.4998 inches and 1.5000 inches

Surface Finish:

Finished

Finished Size Designation:

Standard

Skirt Type:

Solid

Skirt Bottom Cutaway Feature:

Not included

Ring Groove Quantity:

5

Ring Groove Position:

Number 1, number 2, number 2, number 4 and number 5

Ring Groove Width:

0.2505 inches and 0.2515 inches 4th ring

Ring Groove Diameter:

4.328 inches and 4.338 inches 1st ring

Ring Groove Position Below Piston Pin:

Number 1, number 2, number 2, number 4 and number 5 all rings

Oil Groove:

Not included

Distance From Pin Hole Center To Extreme Top:

Between 3.620 inches and 3.630 inches

Pin Hole Bushing:

Not included

Distance Between Pin Bosses:

Between 1.990 inches and 2.010 inches

Retaining Ring Groove:

Included

Pin:

Not included

Pin Type For Which Designed:

Floating

Ring:

Not included

Carbon Groove:

Not included

Skirt Slot Style:

Groove convex slot

Material:

Aluminum

Material:

Aluminum

Surface Treatment:

Tin

Surface Treatment:

Tin plated

Weight:

Any acceptable

Fsc Application Data:

Engine gasoline, non-aircraft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T267-c