## NSN 2805-00-737-1234

Engine Poppet Valve Tappet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2805-00-737-1234 **Thread Direction:** Right-hand Casehardening Indicator: Casehardened **Concentric Hole Depth:** Between 2.453 inches and 2.515 inches **Concentric Hole Diameter:** Between 0.398 inches and 0.413 inches **Overall Length:** 2.875 inches **Thread Size:** 3/8-24 **Body Outside Diameter:** 0.624 inches **Body Groove Width:** 0.120 inches **Spherical Radius:** 30.000 inches **Screw Thread Series Designator:** Unf Screw Thread Length: Between 0.625 inches and 0.750 inches Flats Length: 0.219 inches Size Designation: Standard **Casehardened Location:** Between 0.490 inches and 0.500 inches **Metallic Hardness Rating And Location:** 

Face **Material And Location:** Steel, aisi/sae 5120 Adjustability: Adjustable **Operation Method:** Mechanical Width Across Flats: 58.0 rockwell c face **Adjusting Device:** Included **Cam End Diameter:** Between 1.302 inches and 1.317 inches

## NSN 2805-00-737-1234

Engine Poppet Valve Tappet - Page 2 of 2



Cam End Height:
Between 0.115 inches and 0.125 inches
Body Groove Diameter:
Between 0.590 inches and 0.595 inches
Distance From Body Groove Center To Cam End:
1.425 inches
Style Designator:
Internal thread and wrenching flats push rod end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T267-f