Engine Poppet Valve Tappet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2805-00-741-2868

Casehardening Indicator:
Casehardened
Concentric Hole Depth:
Between 1.705 inches and 1.725 inches
Concentric Hole Diameter:
Between 1.690 inches and 1.710 inches
Overall Length:
Between 1.895 inches and 1.905 inches
Boss Diameter:
Between 0.490 inches and 0.510 inches
Body Groove Width:
Between 0.590 inches and 0.610 inches
Spherical Radius:
30.000 inches
Size Designation:
Standard
Casehardened Location:
Material And Location:
Steel, cast
Adjustability:
Nonadjustable
Operation Method:
Mechanical
Metallic Hardness Rating And Location:
55.0 rockwell c and 60.0 rockwell c
Cam End Diameter:
Between 1.9170 inches and 1.9172 inches
Distance From Boss Face To Cam End:
Between 0.2100 inches and 0.2119 inches
Body Hole Diameter:
Between 0.240 inches and 0.260 inches
Distance From Body Hole Center To Cam End:
Between 1.250 inches and 1.270 inches
Body Groove Diameter:
Between 1.895 inches and 1.905 inches
Distance From Body Groove Center To Cam End:
Between 0.890 inches and 0.910 inches
Style Designator:
Chamfered, concentric hole push rod end
Fsc Application Data:

Engine, gasoline, nonaircraft



Reference Number Differentiating Characteristics:

As differentiated by distance from boss face to cam end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T267-f