## NSN 2805-00-752-0034

Engine Poppet Valve Tappet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2805-00-752-0034

Case	hard	lening	Indicato	r:
------	------	--------	----------	----

Casehardened

**Concentric Hole Depth:** 

Between 1.705 inches and 1.725 inches

**Concentric Hole Diameter:** 

Between 1.690 inches and 1.710 inches

**Overall Length:** 

Between 1.895 inches and 1.905 inches

**Boss Diameter:** 

Between 0.490 inches and 0.510 inches

**Body Groove Width:** 

Between 0.590 inches and 0.610 inches

**Spherical Radius:** 

30.000 inches

Size Designation:

Standard

**Casehardened Location:** 

**Material And Location:** 

Steel, cast

Adjustability:

Nonadjustable

**Operation Method:** 

Mechanical

**Metallic Hardness Rating And Location:** 

55.0 rockwell c and 60.0 rockwell c

Cam End Diameter:

Between 1.9170 inches and 1.9172 inches

**Distance From Boss Face To Cam End:** 

Between 0.2080 inches and 0.2099 inches

**Body Hole Diameter:** 

Between 0.240 inches and 0.260 inches

**Distance From Body Hole Center To Cam End:** 

Between 1.250 inches and 1.270 inches

**Body Groove Diameter:** 

Between 1.895 inches and 1.905 inches

Distance From Body Groove Center To Cam End:

Between 0.890 inches and 0.910 inches

**Style Designator:** 

Chamfered, concentric hole push rod end

**Fsc Application Data:** 

Engine, gasoline, nonaircraft

## NSN 2805-00-752-0034

Engine Poppet Valve Tappet - Page 2 of 2



Reference	Number	Differentiating	Characteristics

As differentiated by distance from boss face to cam end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T267-f