

View Online at <https://aerobasegroup.com/nsn/2805-00-753-9845>

Countersink Angle In Deg:

90.0

Shoulder Diameter:

Between 0.778 inches and 0.785 inches

Shoulder Length:

0.160 inches

Overall Length:

2.750 inches

Outside Diameter:

1.120 inches

Taper Length:

Between 0.190 inches and 0.250 inches

Taper Minor Diameter:

0.770 inches

Bore Diameter:

Between 0.5500 inches and 0.5520 inches

Metallic Hardness Rating:

97.0 rockwell k

Major Diameter Length:

Between 0.122 inches and 0.128 inches

Countersink Diameter:

0.590 inches

Bore Countersink:

Included

Countersink Location:

Aa end and bb end

Bore Counterbore:

Not included

Aa End Diameter:

Between 0.745 inches and 0.750 inches

Bb End Shank Diameter:

Between 0.772 inches and 0.773 inches

Bb End Chamfer Length:

0.030 inches

Bb End Chamfer Angle In Deg:

45.0

Aa End Chamfer Length:

0.030 inches

Aa End Chamfer Angle In Deg:

45.0

Shoulder First Fillet Radius:

0.030 inches

Shoulder Second Fillet Radius:

0.030 inches

Fillet Step Radius:

0.060 inches

Length From Aa End To Largest Diameter Face:

Between 1.302 inches and 1.308 inches

Material:

Aluminum bronze

Material:

Copper alloy

Style Designator:

Stepped shoulder-tapered shank end

Fsc Application Data:

Engine, gasoline, non-aircraft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T267-e