NSN 2805-00-932-2241

Engine Poppet Valve - Page 1 of 2

Head Style:

Head Height:

Flat



View Online at https://aerobasegroup.com/nsn/2805-00-932-2241

Between 0.1430 inches and 0.1580 inches
Chamfer Angle In Deg:
15.7
Chamfer Length:
Between 0.0020 inches and 0.0100 inches
Outside Diameter:
Between 1.7150 inches and 1.7250 inches
Seat Angle In Deg:
45.0
Stem Style:
Double grooved
Carbon Relief Groove:
Not included
Neck Radius:
0.5800 inches
Stem Length:
Between 4.7444 inches and 4.7794 inches
Stem Diameter:
Between 0.3445 inches and 0.3452 inches
Distance From First Groove To Stem End:
0.2590 inches
Distance From Second Groove To Stem End:
Distance From Second Groove To Stem End: 0.5040 inches
0.5040 inches
0.5040 inches First Groove Diameter:
0.5040 inches First Groove Diameter: Between 0.2970 inches and 0.3030 inches
0.5040 inches First Groove Diameter: Between 0.2970 inches and 0.3030 inches Second Groove Diameter:
0.5040 inches First Groove Diameter: Between 0.2970 inches and 0.3030 inches Second Groove Diameter: Between 0.2970 inches and 0.3030 inches
0.5040 inches First Groove Diameter: Between 0.2970 inches and 0.3030 inches Second Groove Diameter: Between 0.2970 inches and 0.3030 inches First Groove Width:
0.5040 inches First Groove Diameter: Between 0.2970 inches and 0.3030 inches Second Groove Diameter: Between 0.2970 inches and 0.3030 inches First Groove Width: Between 0.0950 inches and 0.1050 inches
0.5040 inches First Groove Diameter: Between 0.2970 inches and 0.3030 inches Second Groove Diameter: Between 0.2970 inches and 0.3030 inches First Groove Width: Between 0.0950 inches and 0.1050 inches Second Groove Width:
0.5040 inches First Groove Diameter: Between 0.2970 inches and 0.3030 inches Second Groove Diameter: Between 0.2970 inches and 0.3030 inches First Groove Width: Between 0.0950 inches and 0.1050 inches Second Groove Width: 0.1050 mils and 0.1150 centimeters
0.5040 inches First Groove Diameter: Between 0.2970 inches and 0.3030 inches Second Groove Diameter: Between 0.2970 inches and 0.3030 inches First Groove Width: Between 0.0950 inches and 0.1050 inches Second Groove Width: 0.1050 mils and 0.1150 centimeters Material And Location:
0.5040 inches First Groove Diameter: Between 0.2970 inches and 0.3030 inches Second Groove Diameter: Between 0.2970 inches and 0.3030 inches First Groove Width: Between 0.0950 inches and 0.1050 inches Second Groove Width: 0.1050 mils and 0.1150 centimeters Material And Location: Steel, federal standard 66, aisi/sae 1041
0.5040 inches First Groove Diameter: Between 0.2970 inches and 0.3030 inches Second Groove Diameter: Between 0.2970 inches and 0.3030 inches First Groove Width: Between 0.0950 inches and 0.1050 inches Second Groove Width: 0.1050 mils and 0.1150 centimeters Material And Location: Steel, federal standard 66, aisi/sae 1041 Metallic Hardness Rating And Location:
0.5040 inches First Groove Diameter: Between 0.2970 inches and 0.3030 inches Second Groove Diameter: Between 0.2970 inches and 0.3030 inches First Groove Width: Between 0.0950 inches and 0.1050 inches Second Groove Width: 0.1050 mils and 0.1150 centimeters Material And Location: Steel, federal standard 66, aisi/sae 1041 Metallic Hardness Rating And Location: 50.0 rockwell c tip err-100
0.5040 inches First Groove Diameter: Between 0.2970 inches and 0.3030 inches Second Groove Diameter: Between 0.2970 inches and 0.3030 inches First Groove Width: Between 0.0950 inches and 0.1050 inches Second Groove Width: 0.1050 mils and 0.1150 centimeters Material And Location: Steel, federal standard 66, aisi/sae 1041 Metallic Hardness Rating And Location: 50.0 rockwell c tip err-100 Special Features:
0.5040 inches First Groove Diameter: Between 0.2970 inches and 0.3030 inches Second Groove Diameter: Between 0.2970 inches and 0.3030 inches First Groove Width: Between 0.0950 inches and 0.1050 inches Second Groove Width: 0.1050 mils and 0.1150 centimeters Material And Location: Steel, federal standard 66, aisi/sae 1041 Metallic Hardness Rating And Location: 50.0 rockwell c tip err-100 Special Features: Second groove taper angle 30.0 degree

NSN 2805-00-932-2241

Engine Poppet Valve - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A11200