NSN 2810-00-118-9306

Valve Stem Guide - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2810-00-118-9306

Countersink Angle In Deg:

43.0 and 47.0

Counterbore Diameter:

Between 0.648 inches and 0.658 inches

Counterbore Depth:

Between 0.177 inches and 0.197 inches

Overall Length:

Between 3.146 inches and 3.166 inches

Outside Diameter:

Between 0.990 inches and 1.010 inches

Bore Diameter:

Between 0.6130 inches and 0.6160 inches

Metallic Hardness Rating:

85.0 rockwell f

Major Diameter Length:

Between 0.084 inches and 0.104 inches

Counterbore Location:

Bb end

Countersink Length:

Between 0.021 inches and 0.041 inches

Bore Countersink:

Not included

Countersink Location:

Aa end

Bore Counterbore:

Included

Aa End Diameter:

Between 0.796 inches and 0.802 inches

Bb End Shank Diameter:

Between 0.817 inches and 0.818 inches

Length From Aa End To Largest Diameter Face:

Between 0.759 inches and 0.803 inches

Special Features:

1 external groove, bb end, under flange, 0.037 in. Min, 0.057 in. Maxw, 0.793 in. Min, 0.803 in. Maximum dia

Material:

Bronze, ams 4845 or bronze, ams 4846

Material:

Bronze, ams 4845 or copper alloy 905

Material Specification:

Ams 4846 assn standard 2nd material response

Style Designator:

Plain-shouldered

NSN 2810-00-118-9306

Valve Stem Guide - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

Т267-е