NSN 2810-00-118-9310

Valve Stem Guide - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2810-00-118-9310
Countersink Angle In Deg:
43.0 and 47.00
Counterbore Diameter:
Between 0.648 inches and 0.658 inches
Counterbore Depth:
Between 0.177 inches and 0.197 inches
Overall Length:
Between 3.146 inches and 3.166 inches
Outside Diameter:
Between 0.990 inches and 1.010 inches
Bore Diameter:
Between 0.6125 inches and 0.6155 inches
Metallic Hardness Rating:
85.0 rockwell f
Major Diameter Length:
Between 0.084 inches and 0.104 inches
Counterbore Location:
Bb end
Countersink Length:
0.041 inches
Bore Countersink:
Included
Countersink Location:
Aa end
Bore Counterbore:
Included
Aa End Diameter:
Between 0.796 inches and 0.802 inches
Bb End Shank Diameter:
Between 0.8335 inches and 0.8345 inches
Length From Aa End To Largest Diameter Face:
Between 0.759 inches and 0.803 inches
Special Features:
1 external groove, bb end, under flange, 0.037 in. Min, 0.057 in. Maxw, 0.793 in. Min, 0.803 in. Maximum dia
Material:
Bronze, ams4846 or ams4845
Material:
Bronze, ams4846 or ams4845
Style Designator:
Plain-shouldered

Fsc Application Data:Engine, acft, reciprocating

NSN 2810-00-118-9310

Valve Stem Guide - Page 2 of 2



_					
CI	~~	14	I i	ife:	
J.	16			HE.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

Т267-е