

View Online at <https://aerobasegroup.com/nsn/2810-00-118-9467>

Counterbore Diameter:

Between 0.575 inches and 0.580 inches

Counterbore Depth:

Between 0.110 inches and 0.150 inches

Overall Length:

Between 3.178 inches and 3.198 inches

Outside Diameter:

Between 0.984 inches and 0.990 inches

Taper Length:

Between 0.240 inches and 0.260 inches

Taper Minor Diameter:

Between 0.646 inches and 0.666 inches

Bore Diameter:

Between 0.5520 inches and 0.5550 inches

Metallic Hardness Rating:

85.0 rockwell f

Major Diameter Length:

Between 0.073 inches and 0.083 inches

Counterbore Location:

Aa end

Bore Countersink:

Not included

Bore Counterbore:

Included

Aa End Diameter:

Between 0.778 inches and 0.784 inches

Bb End Shank Diameter:

Between 0.719 inches and 0.720 inches

Bb End Radius:

Between 0.020 inches and 0.040 inches

Shoulder First Fillet Radius:

Between 0.040 inches and 0.050 inches

Shoulder Second Fillet Radius:

Between 0.040 inches and 0.050 inches

Length From Aa End To Largest Diameter Face:

Between 0.761 inches and 0.771 inches

Material:

Copper alloy

Material:

Copper alloy

Style Designator:

Plain-shouldered

Fsc Application Data:

Aircraft eng r2000

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T267-e