## NSN 2810-00-118-9468

Valve Stem Guide - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2810-00-118-9468

Counterbore	Diameter:
-------------	-----------

Between 0.575 inches and 0.580 inches

**Counterbore Depth:** 

Between 0.110 inches and 0.150 inches

**Overall Length:** 

Between 3.178 inches and 3.198 inches

**Outside Diameter:** 

Between 0.984 inches and 0.990 inches

**Taper Length:** 

Between 0.240 inches and 0.260 inches

**Taper Minor Diameter:** 

Between 0.646 inches and 0.666 inches

**Bore Diameter:** 

Between 0.5520 inches and 0.5550 inches

**Major Diameter Length:** 

Between 0.073 inches and 0.083 inches

**Counterbore Location:** 

Aa end

**Bore Countersink:** 

Not included

**Bore Counterbore:** 

Included

Aa End Diameter:

Between 0.778 inches and 0.784 inches

**Bb End Shank Diameter:** 

Between 0.722 inches and 0.723 inches

**Bb End Radius:** 

Between 0.020 inches and 0.040 inches

**Shoulder First Fillet Radius:** 

Between 0.040 inches and 0.050 inches

**Shoulder Second Fillet Radius:** 

Between 0.040 inches and 0.050 inches

**Length From Aa End To Largest Diameter Face:** 

Between 0.761 inches and 0.771 inches

Material:

Copper alloy

Material:

Copper alloy

Style Designator:

Plain-shouldered

**Fsc Application Data:** 

Aircraft eng r2000

## NSN 2810-00-118-9468

Valve Stem Guide - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

Т267-е