

View Online at https://aerobasegroup.com/nsn/2810-00-156-8846

| Head Style: |
|---|
| Flat |
| Overall Height: |
| Between 3.498 inches and 3.504 inches |
| Diameter: |
| 5.1180 inches |
| Pinhole Diameter: |
| Between 1.1249 inches and 1.1252 inches |
| Surface Finish: |
| Finished |
| Finished Size Designation: |
| Standard |
| Skirt Type: |
| Solid |
| Cut Depth: |
| Between 0.509 inches and 0.510 inches |
| Skirt Bottom Cutaway Feature: |
| Included |
| Ring Groove Quantity: |
| 3 |
| Ring Groove Position: |
| No. 1, no. 2 and no. 3 |
| Ring Groove Width: |
| 0.1570 inches and 0.1580 inches 3rd ring |
| Groove Taper Angle: |
| 7 degrees 30 min porm 0 degrees 5 min |
| Ring Groove Diameter: |
| 4.5580 inches and 4.5680 inches 3rd ring |
| Oil Groove: |
| Not included |
| Distance From Pin Hole Center To Extreme Top: |
| Between 2.049 inches and 2.054 inches |
| Pin Hole Bushing: |
| Not included |
| Distance Between Pin Bosses: |
| 1.750 inches |
| Retaining Ring Groove: |
| Not included |
| Pin: |
| Not included |
| Pin Type For Which Designed: |
| Floating |
| |



Ring:

Not included

Carbon Groove:

Not included

Material:

Aluminum

Material:

Aluminum

Weight:

Any acceptable

Fsc Application Data:

Engine, acft, reciprocating

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T267-c