

View Online at <https://aerobasegroup.com/nsn/2810-00-306-6392>

Shoulder Diameter:

Between 0.733 inches and 0.740 inches

Shoulder Length:

0.062 inches

Overall Length:

Between 3.302 inches and 3.322 inches

Outside Diameter:

Between 0.990 inches and 1.010 inches

Taper Length:

Between 0.615 inches and 0.635 inches

Taper Minor Diameter:

Between 0.552 inches and 0.572 inches

Bore Diameter:

Between 0.4275 inches and 0.4305 inches

Metallic Hardness Rating:

85.0 rockwell f

Major Diameter Length:

Between 0.084 inches and 0.104 inches

Countersink Length:

0.031 inches

Bore Countersink:

Included

Countersink Location:

Aa end

Bore Counterbore:

Not included

Aa End Diameter:

Between 0.615 inches and 0.635 inches

Bb End Shank Diameter:

Between 0.636 inches and 0.637 inches

Length From Aa End To Largest Diameter Face:

Between 0.864 inches and 0.884 inches

Special Features:

1 external groove, bb end, under flange, 0.037 in. Min, 0.057 in. Maximum w, 0.606 in. Min, 0.616 in. Maximum diameter groove

Material:

Bronze, ams 4846

Material:

Copper alloy 905

Material Specification:

Ams 4846 assn standard 1st material response

Style Designator:

Stepped shoulder-tapered shank end

Fsc Application Data:

Engine, acft, reciprocating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T267-e