

View Online at <https://aerobasegroup.com/nsn/2810-00-306-6392>

**Shoulder Diameter:**

Between 0.733 inches and 0.740 inches

**Shoulder Length:**

0.062 inches

**Overall Length:**

Between 3.302 inches and 3.322 inches

**Outside Diameter:**

Between 0.990 inches and 1.010 inches

**Taper Length:**

Between 0.615 inches and 0.635 inches

**Taper Minor Diameter:**

Between 0.552 inches and 0.572 inches

**Bore Diameter:**

Between 0.4275 inches and 0.4305 inches

**Metallic Hardness Rating:**

85.0 rockwell f

**Major Diameter Length:**

Between 0.084 inches and 0.104 inches

**Countersink Length:**

0.031 inches

**Bore Countersink:**

Included

**Countersink Location:**

Aa end

**Bore Counterbore:**

Not included

**Aa End Diameter:**

Between 0.615 inches and 0.635 inches

**Bb End Shank Diameter:**

Between 0.636 inches and 0.637 inches

**Length From Aa End To Largest Diameter Face:**

Between 0.864 inches and 0.884 inches

**Special Features:**

1 external groove, bb end, under flange, 0.037 in. Min, 0.057 in. Maximum w, 0.606 in. Min, 0.616 in. Maximum diameter groove

**Material:**

Bronze, ams 4846

**Material:**

Copper alloy 905

**Material Specification:**

Ams 4846 assn standard 1st material response

**Style Designator:**

Stepped shoulder-tapered shank end

**Fsc Application Data:**

Engine, acft, reciprocating

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T267-e