NSN 2810-00-709-3561

Valve Stem Guide - Page 1 of 2

Bb End Radius:

Material:
Copper alloy
Material:
Copper alloy

Between 0.020 inches and 0.040 inches

Between 0.040 inches and 0.050 inches

Between 0.040 inches and 0.050 inches

Between 0.845 inches and 0.851 inches

Length From Aa End To Largest Diameter Face:

Shoulder First Fillet Radius:

Shoulder Second Fillet Radius:



View Online at https://aerobasegroup.com/nsn/2810-00-709-3561
Countersink Angle In Deg:
14.0
Counterbore Diameter:
Between 0.635 inches and 0.640 inches
Counterbore Depth:
Between 0.110 inches and 0.150 inches
Overall Length:
Between 3.260 inches and 3.280 inches
Outside Diameter:
Between 1.090 inches and 1.096 inches
Bore Diameter:
Between 0.6075 inches and 0.6105 inches
Metallic Hardness Rating:
85.0 rockwell f
Major Diameter Length:
Between 0.073 inches and 0.083 inches
Countersink Diameter:
0.698 inches
Counterbore Location:
Aa end
Bore Countersink:
Included
Countersink Location:
Bb end
Bore Counterbore:
Included
Aa End Diameter:
Between 0.935 inches and 0.941 inches
Bb End Shank Diameter:
Between 0.8815 inches and 0.8825 inches

NSN 2810-00-709-3561

Valve Stem Guide - Page 2 of 2



Style	Design	nator:

Plain-shouldered

Fsc Application Data:

Aircraft eng r2800

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T267-e