NSN 2815-00-034-4701

Engine Poppet Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2815-00-034-4701 **Head Style:** Flat **Head Height:** Between 0.1840 inches and 0.1940 inches **Chamfer Angle In Deg:** 45.0 **Chamfer Length:** Between 0.0150 inches and 0.0300 inches **Outside Diameter:** 1.2630 inches **Minor Outside Diameter:** 0.3080 inches **Minor Diameter Length:** 0.7500 inches Seat Angle In Deg: 30.0 Stem Style: Double grooved **Carbon Relief Groove:** Not included **Neck Radius:** 0.4062 inches Stem Length: Between 5.8350 inches and 5.8500 inches Stem Diameter: 0.3410 inches **Distance From First Groove To Stem End:** Between 0.3320 inches and 0.3630 inches **Distance From Second Groove To Stem End:** Between 0.7400 inches and 0.7600 inches **First Groove Diameter:** Between 0.2400 inches and 0.2460 inches **Second Groove Diameter:** Between 0.2400 inches and 0.4060 inches **First Groove Width:** 0.0625 inches **Second Groove Width:** 0.0625 inches

Material And Location: Steel, corrosion resisting head **Special Features:** Used on cumming diesel engines; mdl jn, jns, jt

NSN 2815-00-034-4701

Engine Poppet Valve - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A11200