

View Online at <https://aerobasegroup.com/nsn/2815-00-111-6992>

**Cylinder Quantity:**

8

**Standard Bore Diameter:**

4.250 inches

**Cooling Medium:**

Liquid

**Fording Feature:**

Not included

**Accessory Components And Quantity:**

Air silencers 2; cooler, fresh water 1; cooler, lubricating oil 1; cooler, reduction gear lubricating oil 1; filter, fuel oil 1; filter, lubricating oil 1; filter, reduction gear lubricating oil 1; governor, limiting speed 1; pan, oil 1; pump, fresh water 1; pump, fuel transfer 1; pump, lubricating oil 1; pump, reverse gear lubricating oil 1; pump, sea water 1; strainer, reduction gear lubricating oil 1; tank, expansion water 1

**Reverse Speed Quantity:**

1

**Cylinder Arrangement:**

Single v-type

**Stroke Length:**

5.000 inches

**Strokes Per Cycle:**

2

**Brake Horsepower At Specificationified Rpm:**

250 bhp at 2100 rpm

**Direct Raw Water Cooling Feature:**

Not included

**Closed System Hull Cooling Feature:**

Not included

**Piston Action Type:**

Single acting

**Multifuel Usage Feature:**

Not provided

**Crankshaft Rotation Direction:**

Counterclockwise

**Direct Reversible Feature:**

Not included

**Starting Method:**

Electrical

**Supercharger:**

Not included

**Flywheel:**

Included

**Flywheel Housing:**

Included

**Reduction Gear:**

Included

**Fluid Coupling:**

Not included

**Transmission:**

Included

**Transmission Type:**

Hydraulically actuated

**Speed Range Quantity:**

1

**Forward Speed Quantity Per Range:**

1

**Cross Drive:**

Not included

**Clutch:**

Included

**Main Power Takeoff Rotation Direction:**

Clockwise

**Reduction Gear Ratio:**

1.5 to 1

**Engineheight:**

45.250 inches

**Enginelength:**

61.750 inches

**Enginewidth:**

45.500 inches

**Starter:**

Included

**Voltage In Volts:**

24.0

**Reference Number Differentiating Characteristics:**

As differentiated by w/70 cu mm injectors

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T197-a