NSN 2815-00-132-8622



Diesel Engine - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/2815-00-132-8622 **Cylinder Quantity: Standard Bore Diameter:** 3.625 inches **Cooling Medium:** Liquid **Fording Feature:** Not included **Accessory Components And Quantity:** 1 air cleaner, 1 base, mtg, 1 filter, fuel oil, 1 filter, lubricating oil, 1 generator, battery charger, 1 governor, speed regulator, 1 pan, oil, 1 pump, fresh water, 1 pump, fuel injection, 1 pump, fuel transfer, 1 pump, lubricating oil, 1 pump, sea water **Reverse Speed Quantity:** 1 **Cylinder Arrangement:** Straight in-line Stroke Length: 4.500 inches **Strokes Per Cycle: Brake Horsepower At Specificationified Rpm:** 25 bhp at 1428 rpm **Direct Raw Water Cooling Feature:** Not included **Closed System Hull Cooling Feature:** Included **Piston Action Type:** Single acting **Multifuel Usage Feature:** Not provided

Crankshaft Rotation Direction:

Clockwise

Direct Reversible Feature:

Not included

Starting Method:

Electrical

Supercharger:

Not included

Flywheel:

Included

Flywheel Housing:

Included

Reduction Gear:

Not included

NSN 2815-00-132-8622

Diesel Engine - Page 2 of 2



Fluid Coupling:
Not included
Transmission:
Included
Transmission Type:
Manual
Forward Speed Quantity:
1
Overdrive:
Not included
Cross Drive:
Not included
Clutch:
Included
Main Power Takeoff Rotation Direction:
Clockwise
Engineheight:
33.500 inches
Enginelength:
44.625 inches
Enginewidth:
Enginewidth: 25.000 inches
25.000 inches
25.000 inches Starter:
25.000 inches Starter: Included
25.000 inches Starter: Included Voltage In Volts:
25.000 inches Starter: Included Voltage In Volts: 24.0
25.000 inches Starter: Included Voltage In Volts: 24.0 Special Features:
25.000 inches Starter: Included Voltage In Volts: 24.0 Special Features: Direct drive
25.000 inches Starter: Included Voltage In Volts: 24.0 Special Features: Direct drive Weight:
25.000 inches Starter: Included Voltage In Volts: 24.0 Special Features: Direct drive Weight: 842.00 pounds
25.000 inches Starter: Included Voltage In Volts: 24.0 Special Features: Direct drive Weight: 842.00 pounds Reference Number Differentiating Characteristics:
25.000 inches Starter: Included Voltage In Volts: 24.0 Special Features: Direct drive Weight: 842.00 pounds Reference Number Differentiating Characteristics: As differentiated by accessory components and quantity, and special features
25.000 inches Starter: Included Voltage In Volts: 24.0 Special Features: Direct drive Weight: 842.00 pounds Reference Number Differentiating Characteristics: As differentiated by accessory components and quantity, and special features Shelf Life:
25.000 inches Starter: Included Voltage In Volts: 24.0 Special Features: Direct drive Weight: 842.00 pounds Reference Number Differentiating Characteristics: As differentiated by accessory components and quantity, and special features Shelf Life: N/a
25.000 inches Starter: Included Voltage In Volts: 24.0 Special Features: Direct drive Weight: 842.00 pounds Reference Number Differentiating Characteristics: As differentiated by accessory components and quantity, and special features Shelf Life: N/a
25.000 inches Starter: Included Voltage In Volts: 24.0 Special Features: Direct drive Weight: 842.00 pounds Reference Number Differentiating Characteristics: As differentiated by accessory components and quantity, and special features Shelf Life: N/a Unit Of Measure:
25.000 inches Starter: Included Voltage In Volts: 24.0 Special Features: Direct drive Weight: 842.00 pounds Reference Number Differentiating Characteristics: As differentiated by accessory components and quantity, and special features Shelf Life: N/a Unit Of Measure: Demilitarization: