NSN 2815-00-195-5622

Diesel Engine - Page 1 of 2

Not included



View Online at https://aerobasegroup.com/nsn/2815-00-195-5622

| Outlinder Overeitten |
|--|
| Cylinder Quantity: |
| 6 |
| Standard Bore Diameter: |
| 5.250 inches |
| Cooling Medium: |
| Liquid |
| Fording Feature: |
| Not included |
| Accessory Components And Quantity: |
| Water pump belt 1; fuel filter 1; fuel injector 6; fuel injection pump 1; turbocharger 1 |
| Cylinder Arrangement: |
| Straight in-line |
| Stroke Length: |
| 6.500 inches |
| Strokes Per Cycle: |
| 4 |
| Brake Horsepower At Specificationified Rpm: |
| 180 bhp at 1700 rpm |
| Direct Raw Water Cooling Feature: |
| Not included |
| Closed System Hull Cooling Feature: |
| Not included |
| Piston Action Type: |
| Single acting |
| Multifuel Usage Feature: |
| Not provided |
| Crankshaft Rotation Direction: |
| Counterclockwise |
| Direct Reversible Feature: |
| Not included |
| Starting Method: |
| Electrical |
| Supercharger: |
| Included |
| Flywheel: |
| Included |
| Flywheel Housing: |
| Included |
| Reduction Gear: |
| Not included |
| Fluid Coupling: |

NSN 2815-00-195-5622

Diesel Engine - Page 2 of 2



| Transmission: |
|--|
| Transmission. |
| Not included |
| Clutch: |
| Not included |
| Main Power Takeoff Rotation Direction: |
| Counterclockwise |
| Starter: |
| Included |
| Voltage In Volts: |
| 24.0 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

T197-a