NSN 2815-00-254-7264

Diesel Engine - Page 1 of 2

Fluid Coupling: Not included



View Online at https://aerobasegroup.com/nsn/2815-00-254-7264

| Cylinder Quantity: |
|--|
| 6 |
| Standard Bore Diameter: |
| 6.250 inches |
| Cooling Medium: |
| Liquid |
| Fording Feature: |
| Not included |
| Accessory Components And Quantity: |
| Oair cleaner 1; cooler, oil 1; cooler, intake air 1; filter, fuel 1; filter, oil 1; governor, speed 1; instrument panel w/instruments 1; pump, |
| fresh water 1; pump, fuel 2; pump, oil 1; pump, salt water 1; speed trup device 1 |
| Cylinder Arrangement: |
| Straight in-line |
| Stroke Length: |
| 8.000 inches |
| Strokes Per Cycle: |
| 4 |
| Brake Horsepower At Specificationified Rpm: |
| 300 bhp at 950 rpm |
| Direct Raw Water Cooling Feature: |
| Not included |
| Closed System Hull Cooling Feature: |
| Included |
| Piston Action Type: |
| Single acting |
| Multifuel Usage Feature: |
| Not provided |
| Crankshaft Rotation Direction: |
| Counterclockwise |
| Direct Reversible Feature: |
| Not included |
| Starting Method: |
| Air |
| Supercharger: |
| Included |
| Flywheel: |
| Included |
| Flywheel Housing: |
| Included |
| Reduction Gear: |
| Not included |

NSN 2815-00-254-7264

Diesel Engine - Page 2 of 2



| Transmission: |
|--|
| Not included |
| Clutch: |
| Not included |
| Main Power Takeoff Rotation Direction: |
| Counterclockwise |
| Engineheight: |
| 65.500 inches |
| Enginelength: |
| 74.750 inches |
| Enginewidth: |
| 43.500 inches |
| Starter: |
| Included |
| Reference Number Differentiating Characteristics: |
| As differentiated by accessory components and quantity |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| T197-a |