## NSN 2815-00-354-4341

Cylinder Sleeve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2815-00-354-4341

Chamfer Angle In Deg:
15.0
Chamfer Length:
0.094 inches
Groove Width:
Between 0.275 inches and 0.281 inches
Overall Length:
12.500 inches
Flange Thickness:
Between 0.378 inches and 0.379 inches
Taper Length:
0.594 inches
Taper Minor Diameter:
Between 5.768 inches and 5.769 inches
Bore Diameter:
Between 5.250 inches and 5.251 inches
Body Length:
9.312 inches
Body Outside Diameter:
5.812 inches
Metallic Hardness Rating:
180.0 brinell standard and 220.0 brinell standard
Flange Outside Diameter:
Between 6.179 inches and 6.181 inches
Design Type:
Wet
Bottom Chamfer Angle In Deg:
45.0
Bottom Chamfer Length:
0.031 inches
Valve Recess:
Not included
Top Inside Chamfer:
Included
Bottom Inside Chamfer:
Included
Top Intake Port:
Not included
Largest Outside Diameter Under Flange:
Between 5.871 inches and 5.872 inches
Largest Outside Diameter Width Under Flange:

2.219 inches

## **NSN 2815-00-354-4341** Cylinder Sleeve - Page 2 of 2



<b>Grooved Portion Outside Diameter:</b>
Between 5.871 inches and 5.872 inches
Grooved Portion Width:
Between 0.712 inches and 0.718 inches
Groove Radius Depth:
Between 0.096 inches and 0.101 inches
Intake Hole:
Not included
Material:
Cast iron
Material:
Cast iron
Fsc Application Data:
Crankcase group, diesel engine
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T267-b