## NSN 2815-00-374-4327



Engine Poppet Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/2815-00-374-4327 **Head Style:** Flat **Head Height:** Between 0.1750 inches and 0.1900 inches **Chamfer Angle In Deg:** 45.0 **Chamfer Length:** 0.0200 inches **Outside Diameter:** Between 1.7400 inches and 1.7500 inches Seat Angle In Deg: 30.0 Stem Style: Multi-grooved **Carbon Relief Groove:** 

Included

**Neck Radius:** 

0.5312 inches

Stem Length:

Between 6.7240 inches and 6.7530 inches

Stem Diameter:

Between 0.4020 inches and 0.4030 inches

**Distance From First Groove To Stem End:** 

Between 0.3790 inches and 0.3900 inches

Distance From Second Groove To Stem End:

Between 0.5340 inches and 0.5470 inches

**Distance From Third Groove To Stem End:** 

Between 4.3830 inches and 4.4110 inches

**First Groove Diameter:** 

Between 0.3000 inches and 0.3100 inches

**Second Groove Diameter:** 

Between 0.3000 inches and 0.3100 inches

Third Groove Diameter:

Between 0.3900 inches and 0.3950 inches

**First Groove Width:** 

Between 0.0302 inches and 0.0322 inches

Second Groove Width:

0.0302 mils and 0.0322 centimeters

**Third Groove Width:** 

0.7500 inches

**Material And Location:** 

Steel

## NSN 2815-00-374-4327

Engine Poppet Valve - Page 2 of 2



Wetailic Hardness Rating And Loca	ic Hardness Rating And	Location:
-----------------------------------	------------------------	-----------

52.0 rockwell c tip err-100

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A11200