## NSN 2815-00-437-3043

Diesel Engine - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2815-00-437-3043
Cylinder Quantity:
4
Standard Bore Diameter:
3.875 inches
Cooling Medium:
Liquid
Fording Feature:
Not included
Accessory Components And Quantity:
Air intake silencer 1; cold starting device 1; cooler, fresh water 1; cooler, oil 1; filter, fuel 1; filter, oil 1; generator, charging 1; governor,
speed 1; instrument panel w/instruments 1; pump, fresh water 1; pump, fuel 1; pump, oil 2; pump, salt water 1; regulator, voltage 1;
strainer, fuel 1; tank, expansion 1
Reverse Speed Quantity:
1
Cylinder Arrangement:
Straight in-line
Stroke Length:
4.000 inches
Strokes Per Cycle:
2
Brake Horsepower At Specificationified Rpm:
100 bhp at 2400 rpm
Direct Raw Water Cooling Feature:
Not included
Closed System Hull Cooling Feature:
Not included
Piston Action Type:
Single acting
Multifuel Usage Feature:
Not provided
Crankshaft Rotation Direction:
Clockwise
Direct Reversible Feature:
Not included
Starting Method:
Electrical
Supercharger:
Not included
Flywheel:
Included
Flywheel Housing:

Included

Included

**Reduction Gear:** 

## **NSN 2815-00-437-3043**Diesel Engine - Page 2 of 2



Florid Consultant
Fluid Coupling:
Not included
Transmission:
Included
Transmission Type:
Hydraulically actuated
Speed Range Quantity:
1
Forward Speed Quantity Per Range:
1
Cross Drive:
Not included
Clutch:
Included
Main Power Takeoff Rotation Direction:
Clockwise
Reduction Gear Ratio:
1.52 to 1
Engineheight:
36.250 inches
Enginelength:
Liginolongui.
59.250 inches
59.250 inches
59.250 inches Enginewidth:
59.250 inches  Enginewidth: 32.750 inches
59.250 inches  Enginewidth: 32.750 inches  Starter:
59.250 inches  Enginewidth: 32.750 inches  Starter: Included
59.250 inches  Enginewidth: 32.750 inches  Starter: Included  Voltage In Volts:
59.250 inches  Enginewidth: 32.750 inches  Starter: Included  Voltage In Volts: 24.000
59.250 inches  Enginewidth: 32.750 inches  Starter: Included  Voltage In Volts: 24.000  Special Features:
59.250 inches  Enginewidth: 32.750 inches  Starter: Included  Voltage In Volts: 24.000  Special Features: Deep oil pan for 17 degrees - 20 degrees maximum installation angle
59.250 inches  Enginewidth: 32.750 inches  Starter: Included  Voltage In Volts: 24.000  Special Features: Deep oil pan for 17 degrees - 20 degrees maximum installation angle  Reference Number Differentiating Characteristics:
59.250 inches  Enginewidth: 32.750 inches  Starter: Included  Voltage In Volts: 24.000  Special Features: Deep oil pan for 17 degrees - 20 degrees maximum installation angle  Reference Number Differentiating Characteristics: Akyd
59.250 inches  Enginewidth: 32.750 inches  Starter: Included  Voltage In Volts: 24.000  Special Features: Deep oil pan for 17 degrees - 20 degrees maximum installation angle  Reference Number Differentiating Characteristics:  Akyd  Shelf Life:
59.250 inches  Enginewidth: 32.750 inches  Starter: Included  Voltage In Volts: 24.000  Special Features: Deep oil pan for 17 degrees - 20 degrees maximum installation angle  Reference Number Differentiating Characteristics: Akyd  Shelf Life: N/a
59.250 inches  Enginewidth: 32.750 inches  Starter: Included  Voltage In Volts: 24.000  Special Features: Deep oil pan for 17 degrees - 20 degrees maximum installation angle  Reference Number Differentiating Characteristics: Akyd  Shelf Life: N/a  Unit Of Measure:
59.250 inches  Enginewidth: 32.750 inches  Starter: Included  Voltage In Volts: 24.000  Special Features: Deep oil pan for 17 degrees - 20 degrees maximum installation angle  Reference Number Differentiating Characteristics: Akyd  Shelf Life: N/a  Unit Of Measure:
59.250 inches  Enginewidth: 32.750 inches  Starter: Included  Voltage In Volts: 24.000  Special Features: Deep oil pan for 17 degrees - 20 degrees maximum installation angle  Reference Number Differentiating Characteristics: Akyd  Shelf Life: N/a  Unit Of Measure: Demilitarization: