NSN 2815-00-494-9334

Diesel Engine - Page 1 of 2

Fluid Coupling: Not included



| View Online at https://aerobasegroup.com/nsn/2815-00-494-9334 |
|---|
| Cylinder Quantity: |
| 6 |
| Standard Bore Diameter: |
| 4.250 inches |
| Cooling Medium: |
| Liquid |
| Fording Feature: |
| Not included |
| Accessory Components And Quantity: |
| Xalternator 1, compressor, air 1, fan 1, fuel, filter/unmtd/ 1, fuel, injector 1, generator 1, governor 1, injection nozzle and line 1, lube oil filter |
| /unmtd/ 1, oil cooler 1, oil filter 1, pump, fuel injection 1, starter, elec 1, vibration damper 1 |
| Cylinder Arrangement: |
| Straight in-line |
| Stroke Length: |
| 5.000 inches |
| Strokes Per Cycle: |
| 4 |
| Brake Horsepower At Specificationified Rpm: |
| 157 bhp at 2200 rpm |
| Direct Raw Water Cooling Feature: |
| Not included |
| Closed System Hull Cooling Feature: |
| Not included |
| Piston Action Type: |
| Single acting |
| Multifuel Usage Feature: |
| Not provided |
| Crankshaft Rotation Direction: |
| Counterclockwise |
| Direct Reversible Feature: |
| Not included |
| Starting Method: |
| Electrical |
| Supercharger: |
| Included |
| Flywheel: |
| Included |
| Flywheel Housing: |
| Included |
| Reduction Gear: |
| Natinglydad |

NSN 2815-00-494-9334Diesel Engine - Page 2 of 2



| Transmission: |
|---|
| Not included |
| Clutch: |
| Not included |
| Main Power Takeoff Rotation Direction: |
| Counterclockwise |
| Engineheight: |
| 39.500 inches |
| Enginelength: |
| 47.500 inches |
| Enginewidth: |
| 30.000 inches |
| Starter: |
| Included |
| Voltage In Volts: |
| 24.0 |
| Weight: |
| 1507.00 pounds |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T197-a |