## NSN 2815-00-528-6060

Valve Spring Retainer Lock - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2815-00-528-6060 **Casehardening Indicator:** Not casehardened **Overall Height:** 0.594 inches **Thread Provision:** Unthreaded Largest Inside Diameter: Between 0.493 inches and 0.497 inches **Largest Outside Diameter:** Between 0.795 inches and 0.799 inches **Minimum Inside Diameter:** 0.402 inches First Ridge Radius: Between 0.045 inches and 0.047 inches Second Ridge Radius: Between 0.045 inches and 0.047 inches Third Ridge Radius: Between 0.045 inches and 0.047 inches **Distance Between First And Second Ridge Centers:** 0.160 inches **Distance Between Second And Third Ridge Centers:** 0.160 inches First Ridge Width: 0.091 inches Second Ridge Width: 0.091 inches Third Ridge Width: 0.091 inches **Outside Included Angle In Deg:** 14.25 Material: Steel, sae 1010, fscm 81343 Material: Steel, sae 1010, fscm 81343 **Style Designator:** Straight bore w/three ridges Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 2815-00-528-6060

Valve Spring Retainer Lock - Page 2 of 2



Fiig:

T267-h