NSN 2815-00-528-6073

Valve Spring Retainer Lock - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2815-00-528-6073

view Offilite at https://aerobasegroup.com/hsh/2015-00-52
Casehardening Indicator:
Not casehardened
Overall Height:
Between 0.558 inches and 0.560 inches
Metallic Hardness Rating:
77.0 rockwell b
Thread Provision:
Unthreaded
Largest Inside Diameter:
Between 0.750 inches and 0.755 inches
Largest Outside Diameter:
Between 1.030 inches and 1.032 inches
First Groove Width:
Between 0.190 inches and 0.192 inches
Minimum Inside Diameter:
0.625 inches
Largest Outside Width:
0.200 inches
First Ridge Radius:
0.275 inches
Second Ridge Radius:
0.275 inches
Distance Between First And Second Ridge Centers:
0.323 inches
Distance From Bottom To First Ridge Center:
0.092 inches
Distance From Bottom To First Groove Center:
Between 0.278 inches and 0.279 inches
First Ridge Width:
0.184 inches
Second Ridge Width:
0.184 inches
Outside Included Angle In Deg:
11.0
Material:
Steel, sae 1020
Material:
Steel, sae 1020
Style Designator:
Straight bore w/two ridges
Shelf Life:
NI/a

N/a

NSN 2815-00-528-6073

Valve Spring Retainer Lock - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

T267-h