

View Online at <https://aerobasegroup.com/nsn/2815-00-554-1407>

Cylinder Quantity:

6

Standard Bore Diameter:

4.250 inches

Cooling Medium:

Liquid

Fording Feature:

Not included

Accessory Components And Quantity:

Air cleaner 2, cooler, fresh water 1, cooler, lubricating oil 1, filter, fuel oil 1, filter, lubricating oil 1, governor 1, pan, oil 1, pump, fresh water 1, pump, fuel transfer 1, pump, sea water 1, tank, expansion, water 1

Cylinder Arrangement:

Straight in-line

Stroke Length:

5.000 inches

Strokes Per Cycle:

2

Brake Horsepower At Specificationified Rpm:

165 bhp at 1800 rpm, specified by mfr

Direct Raw Water Cooling Feature:

Not included

Closed System Hull Cooling Feature:

Not included

Piston Action Type:

Single acting

Multifuel Usage Feature:

Not provided

Crankshaft Rotation Direction:

Clockwise

Direct Reversible Feature:

Not included

Starting Method:

Air

Supercharger:

Not included

Flywheel:

Included

Flywheel Housing:

Included

Reduction Gear:

Not included

Fluid Coupling:

Not included

Transmission:

Not included

Clutch:

Not included

Main Power Takeoff Rotation Direction:

Clockwise

Engineheight:

44.250 inches

Enginlength:

50.000 inches

Enginewidth:

27.000 inches

Starter:

Included

Special Features:

Port engine of quad mod 24908

Weight:

2000.00 pounds

Reference Number Differentiating Characteristics:

As differentiated by accessory components and quantity, starting method, and special features

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T197-a