NSN 2815-00-580-4777

Engine Poppet Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2815-00-580-4777

view Online at https://aerobasegroup.com/nsn/281						
Head Style:						
Flat						
Head Height:						
Between 0.1250 inches and 0.1400 inches						
Chamfer Angle In Deg:						
45.0						
Chamfer Length:						
Between 0.0100 inches and 0.0300 inches						
Outside Diameter:						
Between 1.3070 inches and 1.3120 inches						
Seat Angle In Deg:						
30.0						
Stem Style:						
Double grooved						
Carbon Relief Groove:						
Not included						
Neck Radius:						
0.5000 inches						
Stem Length:						
Between 5.7760 inches and 5.8160 inches						
Stem Diameter:						
Between 0.3400 inches and 0.3410 inches						
Distance From First Groove To Stem End:						
Between 0.2988 inches and 0.3288 inches						
Distance From Second Groove To Stem End:						
Between 0.4538 inches and 0.4858 inches						
First Groove Diameter:						
Between 0.2400 inches and 0.2460 inches						
Second Groove Diameter:						
Between 0.2400 inches and 0.2460 inches						
First Groove Width:						
0.0625 inches						
Second Groove Width:						
0.0625 inches						
Material And Location:						
Steel cummins engine co, 33012-01,						
Metallic Hardness Rating And Location:						
52.0 rockwell c tip err-100						
Fsc Application Data:						
Diesel engine						
Shelf Life:						
N/a						

N/a

NSN 2815-00-580-4777

Engine Poppet Valve - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A11200