## NSN 2815-00-618-9930

Diesel Engine - Page 1 of 2

**Reduction Gear:** 

Included



View Online at https://aerobasegroup.com/nsn/2815-00-618-9930

Cylinder Quantity:
12
Standard Bore Diameter:
4.250 inches
Cooling Medium:
Liquid
Fording Feature:
Not included
Accessory Components And Quantity:
Cooler, fresh water 1; cooler, oil 2; filter, fuel oil 1; filter, oil 3; governor, overspeed 1; pan, oil 1; pump, fresh water 1; pump, fuel 1;
pump, sea water 1; tank, expansion 1
Reverse Speed Quantity:
1
Cylinder Arrangement:
Single v-type
Stroke Length:
5.000 inches
Strokes Per Cycle:
2
Brake Horsepower At Specificationified Rpm:
500 bhp at 2100 rpm
Direct Raw Water Cooling Feature:
Not included
Closed System Hull Cooling Feature:
Not included
Piston Action Type:
Single acting
Multifuel Usage Feature:
Not provided
Crankshaft Rotation Direction:
Counterclockwise
Direct Reversible Feature:
Not included
Starting Method:
Electrical
Supercharger:
Included
Flywheel:
Included
Flywheel Housing:
Included

## **NSN 2815-00-618-9930**Diesel Engine - Page 2 of 2



Fluid Coupling:
Not included
Transmission:
Included
Transmission Type:
Hydraulically actuated
Speed Range Quantity:
1
Forward Speed Quantity Per Range:
1
Cross Drive:
Not included
Clutch:
Included
Main Power Takeoff Rotation Direction:
Clockwise
Reduction Gear Ratio:
2.17 to 1
Engineheight:
56.875 inches
Enginelength:
95.000 inches
Enginewidth:
45.500 inches
Starter:
Not included
Special Features:
Turbochargers 2; 80 mm injector; w/1 ether primer cold starting aid; w/intercooler
Weight:
5818.000 pounds
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
T197-a