

View Online at <https://aerobasegroup.com/nsn/2815-00-935-4669>

Cylinder Quantity:

12

Standard Bore Diameter:

4.250 inches

Cooling Medium:

Liquid

Fording Feature:

Not included

Accessory Components And Quantity:

Cooler, fresh water 1; coolers, lubricating oil 2; filter, fuel oil 1; filters, lubricating oil 3; governor, speed regulator 1; pan, oil 1; pump, fresh water 1; pump, fuel transfer 1; pump, lubricating oil 1; pump, sea water 1; strainer, fuel oil 1; tank, expansion water 1

Reverse Speed Quantity:

1

Cylinder Arrangement:

Single v-type

Stroke Length:

5.000 inches

Strokes Per Cycle:

2

Brake Horsepower At Specificationified Rpm:

400 bhp at2100 rpm

Direct Raw Water Cooling Feature:

Not included

Closed System Hull Cooling Feature:

Not included

Piston Action Type:

Single acting

Multifuel Usage Feature:

Not provided

Crankshaft Rotation Direction:

Counterclockwise

Direct Reversible Feature:

Not included

Starting Method:

Electrical

Supercharger:

Not included

Flywheel:

Included

Flywheel Housing:

Included

Reduction Gear:

Included

Fluid Coupling:

Not included

Transmission:

Included

Transmission Type:

Hydraulically actuated

Speed Range Quantity:

1

Forward Speed Quantity Per Range:

1

Cross Drive:

Not included

Clutch:

Included

Main Power Takeoff Rotation Direction:

Counterclockwise

Reduction Gear Ratio:

2.0 to 1

Engineheight:

58.875 inches

Enginelength:

95.000 inches

Enginewidth:

45.500 inches

Starter:

Included

Voltage In Volts:

24.0

Special Features:

W/n70 injectors; w/fuel cooler; cw alternator, 60 amp

Reference Number Differentiating Characteristics:

As differentiated by, modified for high-shock

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T197-a