

View Online at <https://aerobasegroup.com/nsn/2815-01-432-5033>

Cylinder Quantity:

6

Standard Bore Diameter:

3.875 inches

Cooling Medium:

Liquid

End Application:

SANG-LA-V(S-)232

Fording Feature:

Not included

Accessory Components And Quantity:

Four-valve cylinder head 2; flywheel housing 1; flywheel for allison mt600-series transmission 1; engine front upper cover 1; crankshaft pulley 1; aluminum water pump 1; exhaust manifolds 2; fuel pump 1; injectors 6; rocker covers 2; 24-volt starter 1

Cylinder Arrangement:

Single v-type

Stroke Length:

4.500 inches

Strokes Per Cycle:

2

Brake Horsepower At Specificationified Rpm:

275 bhp at 2800rpm

Direct Raw Water Cooling Feature:

Not included

Closed System Hull Cooling Feature:

Not included

Piston Action Type:

Single acting

Multifuel Usage Feature:

Not provided

Crankshaft Rotation Direction:

Clockwise

Direct Reversible Feature:

Not included

Starting Method:

Electrical

Supercharger:

Not included

Flywheel:

Included

Flywheel Housing:

Included

Reduction Gear:

Not included

Fluid Coupling:

Not included

Transmission:

Not included

Clutch:

Not included

Main Power Takeoff Rotation Direction:

Clockwise

Engineheight:

42.260 inches

Enginlength:

40.900 inches

Enginewidth:

36.850 inches

Starter:

Not included

Type/model Designation:

6v53tsilverseries5063539c

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T197-a