

View Online at <https://aerobasegroup.com/nsn/2825-00-188-3340>

Exhaust Pressure:

1.25 pounds per square inch gage

Mounting Position:

Horizontal

Shaft Rotation Direction:

Counterclockwise

Ahead Stage Design:

Reaction

Ahead Rated Horsepower At Specificationified Rpm:

19800 shaft hp at 4301 rpm

Astern Rated Horsepower At Specificationified Rpm:

12000 shaft hp at 3019 rpm

Astern Turbine Location:

Forward end of low pressure turbine or aft end of low pressure turbine

Ahead Reaction Stage Quantity:

9

Ahead Reaction Stage Rotation Blade Row Quantity:

18

Ahead Flow Type:

Double

Astern Stage Design:

Impulse

Astern Rotation Blade Row Quantity:

8

Astern Stationary Blade Row Quantity:

4

Astern Flow Type:

Double

Ahead Initial Steam Gage Pressure:

37.5 pounds per square inch

Astern Initial Steam Gage Pressure:

525.0 pounds per square inch

Ahead Initial Steam Temp:

410.0 degrees fahrenheit

Astern Initial Steam Temp:

825.0 degrees fahrenheit

Reduction Gear Assembled Form:

Separate

Lube Oil Cooler Assembled Form:

Separate

Throttle Valve Assembled Form:

Separate

Reference Number Differentiating Characteristics:

Akct

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T197-c