

View Online at <https://aerobasegroup.com/nsn/2825-00-227-9603>

Exhaust Pressure:

27.50 inches of mercury

Mounting Position:

Horizontal

Shaft Rotation Direction:

Counterclockwise

Ahead Stage Design:

Reaction

Ahead Rated Horsepower At Specificationified Rpm:

1750 shaft hp at 3023 rpm

Astern Rated Horsepower At Specificationified Rpm:

2000 shaft hp at 2000 rpm

Astern Turbine Location:

Forward end of low pressure turbine

Ahead Reaction Stage Quantity:

7

Ahead Reaction Stage Rotation Blade Row Quantity:

18

Ahead Flow Type:

Single

Astern Stage Design:

Impulse

Astern Rotation Blade Row Quantity:

5

Astern Stationary Blade Row Quantity:

3

Astern Flow Type:

Single

Ahead Initial Steam Gage Pressure:

12.0 pounds per square inch

Astern Initial Steam Gage Pressure:

229.0 pounds per square inch

Ahead Initial Steam Temp:

244.0 degrees fahrenheit

Astern Initial Steam Temp:

397.0 degrees fahrenheit

Lube Oil Cooler Assembled Form:

Separate

Throttle Valve Assembled Form:

Separate

Reference Number Differentiating Characteristics:

Akct

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T197-c