NSN 2825-00-227-9613

Steam Turbine - Page 1 of 2



227-9613

View Online at https://aerobasegroup.com/nsn/2825-00-2
Exhaust Pressure:
28.50 inches of mercury
Mounting Position:
Horizontal
Shaft Rotation Direction:
Clockwise
Ahead Rated Horsepower At Specificationified Rpm:
3000 shaft hp at 4048 rpm
Astern Rated Horsepower At Specificationified Rpm:
2550 shaft hp at 2024 rpm
Astern Turbine Location:
Forward end of low pressure turbine
Ahead Flow Type:
Single
Astern Stage Design:
Impulse
Astern Rotation Blade Row Quantity:
3
Astern Stationary Blade Row Quantity:
1
Astern Flow Type:
Single
Ahead Initial Steam Gage Pressure:
22.0 pounds per square inch
Astern Initial Steam Gage Pressure:
325.0 pounds per square inch
Ahead Initial Steam Temp:
325.0 degrees fahrenheit
Astern Initial Steam Temp:
730.0 degrees fahrenheit
Reduction Gear Assembled Form:
Separate
Lube Oil Cooler Assembled Form:
Separate
Throttle Valve Assembled Form:
Separate
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 2825-00-227-9613

Steam Turbine - Page 2 of 2

Fiig: T197-c

