NSN 2825-00-227-9615

Steam Turbine - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2825-00-227-9615

Exhaust Pressure:
2.55 pounds per square inch gage
Mounting Position:
Horizontal
Shaft Rotation Direction:
Clockwise
Ahead Stage Design:
Impulse
Ahead Rated Horsepower At Specificationified Rpm:
15400 shaft hp at 4792 rpm
Astern Rated Horsepower At Specificationified Rpm:
6000 shaft hp at 2571 rpm
Astern Turbine Location:
Forward end of low pressure turbine or aft end of low pressure turbine
Ahead Impulse Stage Quantity:
6
Ahead Impulse Stage Rotation Blade Row Quantity:
12
Ahead Flow Type:
Double
Astern Stage Design:
Impulse
Astern Rotation Blade Row Quantity:
4
Astern Stationary Blade Row Quantity:
2
Astern Flow Type:
Double
Ahead Initial Steam Gage Pressure:
42.0 pounds per square inch
Astern Initial Steam Gage Pressure:
525.0 pounds per square inch
Ahead Initial Steam Temp:
416.0 degrees fahrenheit
Astern Initial Steam Temp:
675.0 degrees fahrenheit
Lube Oil Cooler Assembled Form:
Separate
Throttle Valve Assembled Form:
Separate
Shelf Life:

N/a

NSN 2825-00-227-9615

Steam Turbine - Page 2 of 2



			ıre:

--

Demilitarization:

No

Fiig:

T197-c