

View Online at <https://aerobasegroup.com/nsn/2835-00-076-6503>

General Description:

C/o 1 each rocker arm, investment casting cres ems 555 17-4 ph, cross-shaped as viewed from top, length data, rounded ends with hole in each end, 0.948 in. Min 0.952 in. Maximum lg from center of hole to center of hole, 0.180 in. Min 0.200 in. Maximum width, cross section data, squared ends, 0.473 in. Min 0.477 in. Maximum distance from center of cross to center of each hole, 0.125 in. Min 0.135 in. Maximum width, u-shaped withears as viewed from side, over-all width 0.369 in. Min 0.373 in. Max, 1 eachpin, cres ams 5643 17-4 ph, 0.229 in. Min 0.249 in. Maximum lg, head data, 0.120 in. Min 0.130 in. Maximum lg, 0.1256 in. Min 0.1262 in. Maximum dia, shank data, 0.109 in. Min 0.119 in. Maximum lg, 0.044 in. Min 0.048 in. Maximum dia, 1 each pin, cres ams 5643 17-4 ph, 0.169 in. Min 0.185 in. Maximum lg, head data, 0.060 in. Min 0.066 in. Maximum lg, 0.1256 in. Min 0.1262 in. Maximum dia, shank data, 0.109 in. Min0.119 in. Maximum lg, 0.044 in. Min 0.048 in. Maximum dia

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No