

View Online at <https://aerobasegroup.com/nsn/2840-00-176-3745>

End Application:

T-53 series engines

Special Features:

Titanium alloy m3403, fscm 91547, shot peened ams2430, 36 blades, 13.048 in. Min, 13.051 in. Maximum od, 4.8694 in. Min, 4.8700 in. Maximum id bore, 12 holes 0.337 in. Min, 0.344 in. Maximum diameter on 5.440 in. Nom bolt circle dia, 3 thd holes on 5.440 in. Nom bolt circle dia, 0.250-28unf class 2b thd, thd holes countersunk 90 degrees by 0.280 in. Nom dia, 12 holes 0.154 in. Min, 0.159 in. Maximum diameter 0.150 in. Nom deep on 5.290 in. Nom bolt circle dia.

General Description:

Titanium alloy m3403, fscm 91547, shot peened ams2430, 36 blades, 13.048 in. Min, 13.051 in. Maximum od, 4.8694 in. Min, 4.8700 in. Maximum id bore, 12 holes 0.337 in. Min, 0.344 in. Maximum diameter on 5.440 in. Nom bolt circle dia, 3 thd holes on 5.440 in. Nom bolt circle dia, 0.250-28unf class 2b thd, thd holes countersunk 90 degrees by 0.280 in. Nom dia, 12 holes 0.154 in. Min, 0.159 in. Maximum diameter 0.150 in. Nom deep on 5.290 in. Nom bolt circle dia

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A23900