

View Online at <https://aerobasegroup.com/nsn/2840-00-895-9325>

General Description:

Filter, cres ams5637, rockwell c scale 26 min, 34 maximum hardness, plug, steel ams5070, rockwell c scale 42 min, 72 maximum hardness, 1.400 in. Min, 1.410 in. Maximum o/a lg, 0.180 in. Nom id, 0.900 in. Nom lg id, 1st end round 0.365 in. Min, 0.370 in. Maximum diameter w/6 slots, 0.040 in. Nom w, 0.040 in. Nom depth, slots equally spaced on 1st end face, 0.270 in. Nom diameter 1st step 1st end, 0.250 in. Nom lg 1st step 1st end, external flange 2nd step 1st end, 0.365 in. Min, 0.370 in. Maximum diameter flange, 0.050 in. Nom lg flange, 0.270 in. Nom diameter 3rd step 1st end, 0.270 in. Nom lg 3rd step 1st end, external flange 4th step 1st end, 0.410 in. Nom diameter flange, 0.050 in. Nom lg flange, ext thd 5th step 1st end, 0.500 in.-20 unf series cl 3a thd, undercut 6th step 1st end, 0.075 in. Min, 0.090 in. Maximum lg undercut, 0.424 in. Min, 0.429 in. Maximum diameter undercut, 2nd end hex hd, 0.741 in. Min, 0.752 in. Maximum w across flats, head recessed at center, 0.500 in. Nom diameter by 0.130 in. Nom depth recess, 6 holes 0.065 in. Min, 0.075 in. Maximum diameter through head equal

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No