

View Online at <https://aerobasegroup.com/nsn/2840-01-011-5045>

Special Features:

Surface, phosphate ams 2481; 5.5635 in. O/a lg.; 6.312 in. Min., 6.313 in. Max. O/a dia.; flange located on one end; rockwell c scale 23 maximum hardness; 1.380 in. Min., 1.390 in. Max. O/a lg.; 6.440 in. O/a dia.; 0.420 in. W of face; 1st step 0.670 in. Min., 0.690 in. Max. Lg.; 3.800 in. Od; 2nd step 0.140 in. Min., 0.150 in. Max. Lg.; 4.901 in. Min., 4.903 in. Max. Od; 3rd step 0.140 in. Lg.; 5.000 in. Od; bore, 3.140 in. Id; 0.820 in. Min., 0.830 in. Max. Dp; counterbore, 4.620 in. Id; 0.560 in. Dp; flange located on opposite end; rockwell c scale 23 max. Hardness; 1.430 in. O/a lg; 6.060 in. O/a dia.; 0.320 in. W of face; 1st step 0.780 in. Min., 0.790 in. Max. Lg.; 3.800 in. Od; 2nd step 0.180 in. Min., 0.200 in. Max. Lg.; 4.901 in. Min., 4.903 in. Max. Od; 3rd step 0.130 in. Min., 0.140 in. Max. Lg.; 5.000 in. Od; bore, 3.140 in. Id; 0.780 in. Min., 0.790 in. Max. Dp; counterbor, 4.620 in. Id; 0.460 in. Dp; each flang, 15 holes 0.440 in. Dia.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A530f0