

View Online at <https://aerobasegroup.com/nsn/2840-01-023-3162>

General Description:

Cres, ams5662, rockwell c scale 35.5 min hardness, chrome finish ams2406, 23.709 in. Nom o/a lg, stepped od, 3.3465 in. Min, 3.3468 in. Maximum largest od body, 1st end, ext thd, 2.5625 in.-16 ns series cl 3a thd, 0.286 in. Nom lg thd, 0.383 in. Min, 0.395 in. Maximum distance from 1st end to thd, ext splines, 65 teeth, 30 degrees pressure angle, 2.7083 in. Nom pitch dia, 0.766 in. Min, 0.770 in. Maximum distance from 1st end to splines, ext thd, 3.0937 in.-12 ns series cl 3a thd, 0.950 in. Nom lg thd, 2.123 in. Min, 2.127 in. Maximum distance from 1st end to thd, ext splines, 79 teeth, 30 degrees pressure angle, 3.2917 in. Nom pitch dia, 17.453 in. Min, 17.480 in. Maximum distance from 1st end to splines, 2nd end, ext thd, 3.2812 in.-16 ns series cl 3a thd, 0.390 in. Nom lg thd, ext splines, 106 teeth, 30 degrees pressure angle, 3.3125 in. Nom pitch dia, 0.560 in. Min, 0.570 in. Maximum distance from 2nd end to splines, shoulder, 3.830 in. Min, 3.840 in. Maximum od, 5.580 in. Nom distance from 2nd end to shoulder

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli