NSN 2840-01-034-5821

Outer Ring Coupling - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2840-01-034-5821

	-			
End	Λn	nlic	· atic	۱n:
LIIU	Δ	DIIL	,auc	,,,,

Aircraft engine tf34-ge-100

General Description:

 $15.897 \ \text{in. Min} \ 15.899 \ \text{in. Maximum outside dia, } \ 1.498 \ \text{in. Min} \ 1.508 \ \text{in. Maximum w, } \ 10.595 \ \text{in. Min} \ 10.605 \ \text{in. Maximum inside dia, } \ 0.495 \ \text{in. Maximum outside dia, } \ 0.495 \ \text{in. Min} \ 10.605 \ \text{in. Maximum inside dia, } \ 0.495 \ \text{in. Min} \ 10.605 \ \text{in. Maximum outside dia, } \ 0.495 \ \text{in. Min} \ 10.605 \ \text{in. Maximum outside dia, } \ 0.495 \ \text{in. Min} \ 10.605 \ \text{in. Maximum outside dia, } \ 0.495 \ \text{in. Min} \ 10.605 \ \text{in. Maximum outside dia, } \ 0.495 \ \text{in. Min} \ 10.605 \ \text{in. Maximum outside dia, } \ 0.495 \ \text{in. Min} \ 10.605 \ \text{in. Maximum outside dia, } \ 0.495 \ \text{in. Min} \ 10.605 \ \text{in. Maximum outside dia, } \ 0.495 \ \text{in. Min} \ 10.605 \ \text{in. Maximum outside dia, } \ 0.495 \ \text{in. Min} \ 10.605 \ \text{in. Maximum outside dia, } \ 0.495 \ \text{in. Min} \ 10.605 \ \text{in. Maximum outside dia, } \ 0.495 \ \text{in. Min} \ 10.605 \ \text{in. Maximum outside dia, } \ 0.495 \ \text{in. Min} \ 10.605 \ \text{in. Maximum outside dia, } \ 0.495 \ \text{in. Min} \ 10.605 \ \text{in. Maximum outside dia, } \ 0.495 \ \text{in. Min} \ 10.605 \ \text{in. Maximum outside dia, } \ 0.495 \ \text{in. Min} \ 10.605 \ \text{in. Maximum outside dia, } \ 0.495 \ \text{in. Min} \ 10.605 \ \text{in. Min} \ 10.605 \ \text{in. Maximum outside dia, } \ 0.495 \ \text{in. Min} \ 10.605 \ \text{in. Min} \ 10.60$

Min 0.505 in. Maximum w of inside

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli