

View Online at <https://aerobasegroup.com/nsn/2840-01-037-9316>

General Description:

Magnesium, ems44500 fscm 73342, 6.6750 in. Nom o/a lg, 2.440 in. Nom o/a w, 0.530 in. Nom o/a thk, w/pressed in bushing, 0.4395 in. Min, 0.4405 in. Maximum id bushing, 1.718 in. Nom distance from 1st end to centerline of bushing, 4 holes 0.217 in. Min, 0.225 in. Maximum diameter through body along lg, 1.8124 in. Nom c to c distance between holes along w, 2 holes 0.217 in. Min, 0.225 in. Maximum diameter through body, 1.7398 in. Nom c to c distance between holes along w, 1 hole 0.217 in. Min, 0.225 in. Maximum diameter through body at centerline, 0.812 in. Nom distance from 1st end to hole center, 1 hole 0.217 in. Min, 0.225 in. Maximum diameter through body offset from centerline, 0.220 in. Nom distance from 2nd end to hole center, 2 holes through body along w countersunk to 0.416 in. Nom dia, 1.8124 in. Nom c to c distance between holes, 2.8185 in. Nom distance from 1st end to hole centers, 1 hole 0.1882 in. Min, 0.1892 in. Maximum diameter through body at centerline, 0.343 in. Nom distance from 1st end to hole center, 1 hole 0.1882 in. Min, 0.1892 in

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No