

View Online at <https://aerobasegroup.com/nsn/2840-01-039-3339>

General Description:

Tube, cres, ams5571 or ams5575, 0.018 in. Min, 0.022 in. Maximum wall thk, 16.775 in. Nom o/a lg, tapered od, 1st end ext flange, cres, ams5646, 2.927 in. Min, 2.935 in. Maximum od flange, 0.400 in. Nom w flange, 1 ext groove on flange od, 0.182 in. Min, 0.187 in. Maximum w by 0.162 in. Min, 0.178 in. Maximum dp groove, 0.090 in. Min, 0.100 in. Maximum distance from 1st end to groove, 2nd end ext flange, cres, ams5646, 2.187 in. Min, 2.195 in. Maximum od flange, 0.400 in. Nom w flange, 1 ext groove on flange od, 0.182 in. Min, 0.187 in. Maximum w by 0.162 in. Min, 0.178 in. Maximum dp groove, 0.050 in. Min, 0.060 in. Maximum distance from 2nd end to groove, 1 intermediate ext flange, 3.390 in. Min, 3.400 in. Maximum od flange, 0.080 in. Min, 0.110 in. Maximum o/a w flange, 3.225 in. Min, 3.265 in. Maximum distance from 2nd end to flange, tapered id, 2.620 in. Nom id 1st end, 1.880 in. Nom id 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli