

View Online at <https://aerobasegroup.com/nsn/2840-01-041-9245>

General Description:

Steel, ams6323 or ams6322, rockwell c scale 44 min, 48 maximum hardness, 2.278 in. Min, 2.292 in. Maximum o/a lg, 1st end, flange, 3.7125 in. Min, 3.7135 in. Maximum o/a od flange, 0.115 in. Min, 0.125 in. Maximum o/a thk flange, 8 holes 0.188 in. Nom dia, 2 holes 0.230 in. Min, 0.238 in. Maximum diameter and 1 hole 0.280 in. Min, 0.290 in. Maximum diameter through flange on 3.180 in. Nom bolt circle dia, 2nd end, plain, 2.801 in. Min, 2.802 in. Maximum od body, 1 hole 0.312 in. Nom diameter through 1 wall of body, 1.258 in. Min, 1.262 in. Maximum distance from 1st end to hole center, 1 slot through 1 wall of body, 1.000 in. Nom w slot, 0.698 in. Min, 0.702 in. Maximum distance from 1st end to slot, 0.040 in. Lg by 45 degrees chamfer od 2nd end, 2.661 in. Min, 2.667 in. Maximum id, 1 int flange at id 2nd end, 2.515 in. Min, 2.525 in. Maximum id flange, 0.046 in. Min, 0.062 in. Maximum thk flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No