NSN 2840-01-320-0704

Aircraft Gas Turbine Engine Compressor Rotor Spacer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2840-01-320-0704

Special Features:

Fiig: A522x0

1.3680-1.3620 in. Of length is tapered to an outside diameter of 6.4100-6.4120 in. And an inside diameter of 6.2450-6.2550 in.; tapered edge has 6 equally spaced prongs projecting internally w/bolt holes centrally located on each prong w/dia of 0.2620-0.2690 in., prongs are 0.5900-0.6100 in. Wide and 0.6435-0.6475 in. Long; at beginning of taper 6 equally spaced notches are located 0.2400-0.2600 in. Wide and 0.4450-0.4550 in. Long projecting internally; opposite of tapered end are 6 equally spaced prongs projecting internally w/bolt holes centrally located on each prong w/dia of 0.2620-0.2690 in. And chamfered 0.0250-0.0350 in., 45 deg; all bolt holes have 63.0 microinch finish

located on each prong w/dia of 0.2620-0.2690 in. And chamfered 0.0250-0.0350 in., 45 deg; all bolt holes
Material:
Titanium alloy
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No