NSN 2840-01-345-1298

Aircraft Gas Turbine Engine Turbine Disk - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2840-01-345-1298

Overall Length: 10.936 inches Hardness Rating: 38.0 rockwell c and 43.0 rockwell c Product Name: Disk, gas turbine engine Engine Section Location: Compressor Stage Number: 4 Special Features: Internal involute spline data; no. Of teeth 324, pitch 32/64, pressure angle 30 degrees, base circle dia. 8.758 in. Min. Dia., 10.097 in. Pitch dia., 10.125 in. Basic form dia., 10.162 in. Max. Dia., 10.183 in. Dimensions over two 0.054 dia. Pins - 10.048 in. Max. External spline data, no. Of teeth 264 on the basis of 344 pitch 32/64, pressure angle 30 degrees, base circle dia. 9.310 in. Min. Dia., 10.698 in Pitch dia., 1.750 in. Basic, form dia. 10.715 in., splines in accordance with ansi b92.1, dimension over two 0.054 in. Dia., pins = 10.83 Max. Material: Stainless steel Material Specification: Ams5763 federal specification single material response Fsc Application Data: Compressor rotor, turbine Shelf Life:	
Hardness Rating: 38.0 rockwell c and 43.0 rockwell c Product Name: Disk, gas turbine engine Engine Section Location: Compressor Stage Number: 4 Special Features: Internal involute spline data; no. Of teeth 324, pitch 32/64, pressure angle 30 degrees, base circle dia. 8.758 in. Min. Dia., 10.097 in. Pitch dia., 10.125 in. Basic form dia., 10.162 in. Max. Dia., 10.183 in. Dimensions over two 0.054 dia. Pins - 10.048 in. Max. External spline data, no. Of teeth 264 on the basis of 344 pitch 32/64, pressure angle 30 degrees, base circle dia. 9.310 in. Min. Dia., 10.698 in Pitch dia., 1.750 in. Basic, form dia. 10.715 in., splines in accordance with ansi b92.1, dimension over two 0.054 in. Dia., pins = 10.83 Max. Material: Stainless steel Material Specification: Ams5763 federal specification single material response Fsc Application Data: Compressor rotor, turbine	
38.0 rockwell c and 43.0 rockwell c Product Name: Disk, gas turbine engine Engine Section Location: Compressor Stage Number: 4 Special Features: Internal involute spline data; no. Of teeth 324, pitch 32/64, pressure angle 30 degrees, base circle dia. 8.758 in. Min. Dia., 10.097 in. Pitch dia., 10.125 in. Basic form dia., 10.162 in. Max. Dia., 10.183 in. Dimensions over two 0.054 dia. Pins - 10.048 in. Max. External spline data, no. Of teeth 264 on the basis of 344 pitch 32/64, pressure angle 30 degrees, base circle dia. 9.310 in. Min. Dia., 10.698 in Pitch dia., 1.750 in. Basic, form dia. 10.715 in., splines in accordance with ansi b92.1, dimension over two 0.054 in. Dia., pins = 10.83 Max. Material: Stainless steel Material Specification: Ams5763 federal specification single material response Fsc Application Data: Compressor rotor, turbine	
Product Name: Disk, gas turbine engine Engine Section Location: Compressor Stage Number: 4 Special Features: Internal involute spline data; no. Of teeth 324, pitch 32/64, pressure angle 30 degrees, base circle dia. 8.758 in. Min. Dia., 10.097 in. Pitch dia., 10.125 in. Basic form dia., 10.162 in. Max. Dia., 10.183 in. Dimensions over two 0.054 dia. Pins - 10.048 in. Max. External spline data, no. Of teeth 264 on the basis of 344 pitch 32/64, pressure angle 30 degrees, base circle dia. 9.310 in. Min. Dia., 10.698 in Pitch dia., 1.750 in. Basic, form dia. 10.715 in., splines in accordance with ansi b92.1, dimension over two 0.054 in. Dia., pins = 10.83 Max. Material: Stainless steel Material Specification: Ams5763 federal specification single material response Fsc Application Data: Compressor rotor, turbine	
Disk, gas turbine engine Engine Section Location: Compressor Stage Number: 4 Special Features: Internal involute spline data; no. Of teeth 324, pitch 32/64, pressure angle 30 degrees, base circle dia. 8.758 in. Min. Dia., 10.097 in. Pitch dia., 10.125 in. Basic form dia., 10.162 in. Max. Dia., 10.183 in. Dimensions over two 0.054 dia. Pins - 10.048 in. Max. External spline data, no. Of teeth 264 on the basis of 344 pitch 32/64, pressure angle 30 degrees, base circle dia. 9.310 in. Min. Dia., 10.698 in Pitch dia., 1.750 in. Basic, form dia. 10.715 in., splines in accordance with ansi b92.1, dimension over two 0.054 in. Dia., pins = 10.83 Max. Material: Stainless steel Material Specification: Ams5763 federal specification single material response Fsc Application Data: Compressor rotor, turbine	
Engine Section Location: Compressor Stage Number: 4 Special Features: Internal involute spline data; no. Of teeth 324, pitch 32/64, pressure angle 30 degrees, base circle dia. 8.758 in. Min. Dia., 10.097 in. Pitch dia., 10.125 in. Basic form dia., 10.162 in. Max. Dia., 10.183 in. Dimensions over two 0.054 dia. Pins - 10.048 in. Max. External spline data, no. Of teeth 264 on the basis of 344 pitch 32/64, pressure angle 30 degrees, base circle dia. 9.310 in. Min. Dia., 10.698 in Pitch dia., 1.750 in. Basic, form dia. 10.715 in., splines in accordance with ansi b92.1, dimension over two 0.054 in. Dia., pins = 10.83 Max. Material: Stainless steel Material Specification: Ams5763 federal specification single material response Fsc Application Data: Compressor rotor, turbine	
Compressor Stage Number: 4 Special Features: Internal involute spline data; no. Of teeth 324, pitch 32/64, pressure angle 30 degrees, base circle dia. 8.758 in. Min. Dia., 10.097 in. Pitch dia., 10.125 in. Basic form dia., 10.162 in. Max. Dia., 10.183 in. Dimensions over two 0.054 dia. Pins - 10.048 in. Max. External spline data, no. Of teeth 264 on the basis of 344 pitch 32/64, pressure angle 30 degrees, base circle dia. 9.310 in. Min. Dia., 10.698 in Pitch dia., 1.750 in. Basic, form dia. 10.715 in., splines in accordance with ansi b92.1, dimension over two 0.054 in. Dia., pins = 10.83 Max. Material: Stainless steel Material Specification: Ams5763 federal specification single material response Fsc Application Data: Compressor rotor, turbine	
Stage Number: 4 Special Features: Internal involute spline data; no. Of teeth 324, pitch 32/64, pressure angle 30 degrees, base circle dia. 8.758 in. Min. Dia., 10.097 in. Pitch dia., 10.125 in. Basic form dia., 10.162 in. Max. Dia., 10.183 in. Dimensions over two 0.054 dia. Pins - 10.048 in. Max. External spline data, no. Of teeth 264 on the basis of 344 pitch 32/64, pressure angle 30 degrees, base circle dia. 9.310 in. Min. Dia., 10.698 in Pitch dia., 1.750 in. Basic, form dia. 10.715 in., splines in accordance with ansi b92.1, dimension over two 0.054 in. Dia., pins = 10.83 Max. Material: Stainless steel Material Specification: Ams5763 federal specification single material response Fsc Application Data: Compressor rotor, turbine	
Special Features: Internal involute spline data; no. Of teeth 324, pitch 32/64, pressure angle 30 degrees, base circle dia. 8.758 in. Min. Dia., 10.097 in. Pitch dia., 10.125 in. Basic form dia., 10.162 in. Max. Dia., 10.183 in. Dimensions over two 0.054 dia. Pins - 10.048 in. Max. External spline data, no. Of teeth 264 on the basis of 344 pitch 32/64, pressure angle 30 degrees, base circle dia. 9.310 in. Min. Dia., 10.698 in Pitch dia., 1.750 in. Basic, form dia. 10.715 in., splines in accordance with ansi b92.1, dimension over two 0.054 in. Dia., pins = 10.83 Max. Material: Stainless steel Material Specification: Ams5763 federal specification single material response Fsc Application Data: Compressor rotor, turbine	
Special Features: Internal involute spline data; no. Of teeth 324, pitch 32/64, pressure angle 30 degrees, base circle dia. 8.758 in. Min. Dia., 10.097 in. Pitch dia., 10.125 in. Basic form dia., 10.162 in. Max. Dia., 10.183 in. Dimensions over two 0.054 dia. Pins - 10.048 in. Max. External spline data, no. Of teeth 264 on the basis of 344 pitch 32/64, pressure angle 30 degrees, base circle dia. 9.310 in. Min. Dia., 10.698 in Pitch dia., 1.750 in. Basic, form dia. 10.715 in., splines in accordance with ansi b92.1, dimension over two 0.054 in. Dia., pins = 10.83 Max. Material: Stainless steel Material Specification: Ams5763 federal specification single material response Fsc Application Data: Compressor rotor, turbine	
Internal involute spline data; no. Of teeth 324, pitch 32/64, pressure angle 30 degrees, base circle dia. 8.758 in. Min. Dia., 10.097 in. Pitch dia., 10.125 in. Basic form dia., 10.162 in. Max. Dia., 10.183 in. Dimensions over two 0.054 dia. Pins - 10.048 in. Max. External spline data, no. Of teeth 264 on the basis of 344 pitch 32/64, pressure angle 30 degrees, base circle dia. 9.310 in. Min. Dia., 10.698 in Pitch dia., 1.750 in. Basic, form dia. 10.715 in., splines in accordance with ansi b92.1, dimension over two 0.054 in. Dia., pins = 10.83 Max. Material: Stainless steel Material Specification: Ams5763 federal specification single material response Fsc Application Data: Compressor rotor, turbine	
Pitch dia., 10.125 in. Basic form dia., 10.162 in. Max. Dia., 10.183 in. Dimensions over two 0.054 dia. Pins - 10.048 in. Max. External spline data, no. Of teeth 264 on the basis of 344 pitch 32/64, pressure angle 30 degrees, base circle dia. 9.310 in. Min. Dia., 10.698 in Pitch dia., 1.750 in. Basic, form dia. 10.715 in., splines in accordance with ansi b92.1, dimension over two 0.054 in. Dia., pins = 10.83 Max. Material: Stainless steel Material Specification: Ams5763 federal specification single material response Fsc Application Data: Compressor rotor, turbine	
spline data, no. Of teeth 264 on the basis of 344 pitch 32/64, pressure angle 30 degrees, base circle dia. 9.310 in. Min. Dia., 10.698 in Pitch dia., 1.750 in. Basic, form dia. 10.715 in., splines in accordance with ansi b92.1, dimension over two 0.054 in. Dia., pins = 10.83 Max. Material: Stainless steel Material Specification: Ams5763 federal specification single material response Fsc Application Data: Compressor rotor, turbine	1ax.
Pitch dia., 1.750 in. Basic, form dia. 10.715 in., splines in accordance with ansi b92.1, dimension over two 0.054 in. Dia., pins = 10.83 Max. Material: Stainless steel Material Specification: Ams5763 federal specification single material response Fsc Application Data: Compressor rotor, turbine	volu
Material: Stainless steel Material Specification: Ams5763 federal specification single material response Fsc Application Data: Compressor rotor, turbine	Min
Material: Stainless steel Material Specification: Ams5763 federal specification single material response Fsc Application Data: Compressor rotor, turbine	in.
Stainless steel Material Specification: Ams5763 federal specification single material response Fsc Application Data: Compressor rotor, turbine	
Material Specification: Ams5763 federal specification single material response Fsc Application Data: Compressor rotor, turbine	
Ams5763 federal specification single material response Fsc Application Data: Compressor rotor, turbine	
Fsc Application Data: Compressor rotor, turbine	
Compressor rotor, turbine	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
Yes - demil/mli	
Fiig:	
A10700	