Cam Actuated Fuel Pump - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2910-00-212-9081

Norstandard         Overall Length:         3.494 inches         Overall Height:         4.719 inches         Overall Width:         3.124 inches         Actuation Method:         Direct cam         Fording Feature:         Not included         Furnished Items And Quantity:         Gasket 1         Stroke Length:         0.312 inches         Vacuum Booster:         Not included         Fuel Filter:         Not included         Prining Lever:         Not included         Prining Lever:         Not included         Prining Lever:         Not included         Maximum Static Pressure Above Outlet Height:         2.500 psi min to 4.000 psi maximum at 16 in. At 1800 rpm         Distance From Pump Mounting Face To Actuator Center:         1.749 in. To centerline of cam         Inter Connection Type/size:         Fuel 0.125 in. Pipe size         Outlet Connection Type/size:         Fuel 0.125 in. Pipe size         Drain Facility:         Not included         Shelf Life:         N/a         Dint Cof Measure:         Imin	
Overall Length:3.494 inchesOverall Height: <td>Mounting Type:</td>	Mounting Type:
A 494 inches Overall Height: 4.719 inches Overall Width: 3.124 inches Actuation Method: Direct cam Fording Feature: Not included Furnished Items And Quantity: Gasket 1 Stroke Length: 0.312 inches Vacuum Booster: Not included Fuel Filter: Not included Priming Lever: Not included Maximum Static Pressure Above Outlet Height: 2.500 psi min to 4.000 psi maximum at 16 in. At 1800 rpm Distance From Pump Mounting Face To Actuator Center: 1.749 in. To centerline of cam Intet Connection Type/size: Fuel 0.125 in. Pipe size Outlet Connection Type/size: Fuel 0.125 in. Pipe size Distance From Pump Mounting Face To Actuator Center: 1.749 in. To centerline of cam Intet Connection Type/size: Fuel 0.125 in. Pipe size Dutlet Connection Type/size: Fuel 0.125 in. Pipe size Fuel	
Overall Height:4.719 inchesOverall Width:3.124 inchesActuation Method:Direct camFording Feature:Not includedFurnished items And Quantity:Gasket 1Stroke Length:0.312 inchesVacuum Booster:Not includedFurlished items And Quantity:Out includedPartine Booster:Not includedPrining Lever:Not includedPrining Lever:2.500 psi min to 4.000 psi maximum at 16 in. At 1800 rpmDistance From Pump Mounting Face To Actuator Center:1.749 in. To centerline of camIntel Connection Type/size:Fuel 0.125 in. Pipe sizeDutit Connection Type/size:Fuel 0.125 in. Pipe sizeDutit Connection Type/size:Fuel 0.125 in. Pipe sizeDirain Facility:Not includedSheff Life:NaDirain Facility:Na includedFacility:Na includedSheff Life:Na includedFacility:Na includedSheff Life:Na includedSheff Life:Na included	-
A-719 inches Overall Width: 3.124 inches Actuation Method: Direct cam Fording Feature: Not included Furnished Items And Quantity: Gasket 1 Stroke Length: 0.312 inches Vacuum Booster: Not included Fuel Filter: Not included Fuel Filter: Not included Pring Lever: Not included Maximum Static Pressure Above Outlet Height: 2.500 psi min to 4.000 psi maximum at 16 in. At 1800 rpm Distance From Pump Mounting Face To Actuator Center: 1.749 in. To centerline of cam Inlet Connection Type/size: Fuel 0.125 in. Pipe size Dutlet Connection Type/size: Fuel 0.125 in. Pipe size Drain Facility: Not included Sheff Life: Na Unit Of Measure: - Demilitarization: No	
Overall Width:3.124 inchesActuation Method:Direct camFording Feature:Not includedFurnished Items And Quantity:Gasket 1Stroke Length:0.312 inchesVacuum Booster:Not includedFuel Filter:Not includedPrining Lever:Not includedMaximum Static Pressure Above Outlet Height:2.500 psi min to 4.000 psi maximum at 16 in. At 1800 rpmDistance From Pump Mounting Face To Actuator Center:1.749 in. To centerline of camIntel Connection Type/size:Fuel 0.125 in. Pipe sizeOutlet Connection Type/size:Fuel 0.125 in. Pipe sizeDistance From Pump Mounting Face To Actuator Center:1.749 in. To centerline of camIntel Connection Type/size:Fuel 0.125 in. Pipe sizeOutlet Connection Type/size:Fuel 0.125 in. Pipe sizeDirain Facility:Not includedShelf Life:NaDirain Facility:NoFig:NoFig:	-
3.124 inches 3.124 inches Actuation Method: Direct cam Fording Feature: Not included Furnished Items And Quantity: Gasket 1 Stroke Length: 0.312 inches Vacuum Booster: Not included Fuel Filter: Not included Fuel Filter: Not included Maximum Static Pressure Above Outlet Height: 2.500 psi min to 4.000 psi maximum at 16 in. At 1800 rpm Distance From Pump Mounting Face To Actuator Center: 1.749 in. To centerline of cam Intet Connection Type/size: Fuel 0.125 in. Pipe size Outlet Connection Type/size: Fuel 0.125 in. Pipe size Drain Facility: Not included Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	4.719 inches
Actuation Method:   Direct cam   Fording Feature:   Not included   Furnished Items And Quantity:   Gasket 1   Stroke Length:   0.312 inches   Vacuum Booster:   Not included   Fuel Filter:   Not included   Fuining Lever:   Not included   Maximum Static Pressure Above Outlet Height:   2.500 psi min to 4.000 psi maximum at 16 in. At 1800 rpm   Distance From Pump Mounting Face To Actuator Center:   1.749 in. To centerline of cam   Inlet Connection Type/size:   Fuel 0.125 in. Pipe size   Outlet Connection Type/size:   Fuel 0.125 in. Pipe size   Drain Facility:   Not included   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:	
Direct cam Fording Feature: Not included Furnished Items And Quantity: Gasket 1 Gasket 1 Stroke Length: 0.312 inches Vacuum Booster: Not included Fuel Filter: Not included Fuel Filter: Not included Priming Lever: Not included Maximum Static Pressure Above Outlet Height: 2.500 psi min to 4.000 psi maximum at 16 in. At 1800 rpm Distance From Pump Mounting Face To Actuator Center: 1.749 in. To centerline of cam Intel Connection Type/size: Fuel 0.125 in. Pipe size Dutlet Connection Type/size: Fuel 0.125 in. Pipe size Datif Lifte: Not included Shelf Lifte: Not included Fuel Connection Type/size: Fuel 0.125 in. Pipe size Datif Connection Type/size: Fuel 0.125 in. Pipe size Datif Connection Type/size: Fuel 0.125 in. Pipe size Fuel 0.125 in. Pipe size Fuel 0.125 in. Pipe size Datif Connection Type/size: Fuel 0.125 in. Pipe size Fuel 0.125 in.	3.124 inches
Fording Feature:         Not included         Furnished Items And Quantity:         Gasket 1         Stroke Length:         0.312 inches         Vacuum Booster:         Not included         Fuel Filter:         Not included         Priming Lever:         Not included         Maximum Static Pressure Above Outlet Height:         2.500 psi min to 4.000 psi maximum at 16 in. At 1800 rpm         Distance From Pump Mounting Face To Actuator Center:         1.749 in. To centerline of cam         Inlet Connection Type/size:         Fuel 0.125 in. Pipe size         Outlet Connection Type/size:         Fuel 0.125 in. Pipe size         Drain Facility:         Not included         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:         No         Fig:	Actuation Method:
Not included Furnished Items And Quantity: Gasket 1 Gasket 1 Stroke Length: 0.312 inches Vacuum Booster: Not included Fuel Filter: Not included Fuel Filter: Not included Fuel Filter: Not included Maximum Static Pressure Above Outlet Height: 2.500 psi min to 4.000 psi maximum at 16 in. At 1800 rpm Distance From Pump Mounting Face To Actuator Center: 1.749 in. To centerline of cam Intet Connection Type/size: Fuel 0.125 in. Pipe size Outlet Connection Type/size: Fuel 0.125 in. Pipe size Distance In Pipe size Distance In Pipe size Fuel 0.125 in. Pipe size Distance In Pipe size Fuel 0.125 in. Pipe size Distance In Pipe size Fuel 0.125 in. Pipe size Distance In Pipe size Fuel 0.125 in. Pipe size Distance In Pipe size Fuel 0.125 in. Pipe size Distance In Pipe size Fuel 0.125 in. Pipe size Distance In Pipe size Distance In Pipe size Distance In Pipe size Distance In Pipe size Fuel 0.125 in. Pipe size Distance In Pipe size Fuel 0.125 in. Pipe size Distance In Pipe size Fuel 0.125 in. Pipe size Fuel 0.125 in. Pipe size Fuel 0.125 in. Pipe size Distance In Pipe size Fuel 0.125 in. Pi	Direct cam
Furnished Items And Quantity: Gasket 1 Stroke Length: 0.312 inches Vacuum Booster: Not included Fuel Filter: Not included Fuel Filter: Not included Priming Lever: Not included Maximum Static Pressure Above Outlet Height: 2.500 psi min to 4.000 psi maximum at 16 in. At 1800 rpm Distance From Pump Mounting Face To Actuator Center: 1.749 in. To centerline of cam Inlet Connection Type/size: Fuel 0.125 in. Pipe size Outlet Connection Type/size: Fuel 0.125 in. Pipe size Dutlet Connection Type/size: Fuel 0.125 in. Pipe size	Fording Feature:
Gasket 1 Stroke Length: O.312 inches Vacuum Booster: Not included Fuel Filter: Not included Fuel Filter: Not included Priming Lever: Not included Maximum Static Pressure Above Outlet Height: 2.500 psi min to 4.000 psi maximum at 16 in. At 1800 rpm Distance From Pump Mounting Face To Actuator Center: 1.749 in. To centerline of cam Intet Connection Type/size: Fuel 0.125 in. Pipe size Outlet Connection Type/size: Fuel 0.125 in. Pipe size Datin Facility: Not included Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not included
Stroke Length: 0.312 inches Vacuum Booster: Not included Fuel Filter: Not included Priming Lever: Not included Maximum Static Pressure Above Outlet Height: 2.500 psi min to 4.000 psi maximum at 16 in. At 1800 rpm Distance From Pump Mounting Face To Actuator Center: 1.749 in. To centerline of cam Inlet Connection Type/size: Fuel 0.125 in. Pipe size Outlet Connection Type/size: Fuel 0.125 in. Pipe size Drain Facility: Not included Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Furnished Items And Quantity:
0.312 inches Vacuum Booster: Not included Fuel Filter: Not included Priming Lever: Not included Maximum Static Pressure Above Outlet Height: 2.500 psi min to 4.000 psi maximum at 16 in. At 1800 rpm Distance From Pump Mounting Face To Actuator Center: 1.749 in. To centerline of cam Inlet Connection Type/size: Fuel 0.125 in. Pipe size Outlet Connection Type/size: Fuel 0.125 in. Pipe size Distance From Pump Mounting Face To Actuator Center: Not included Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Gasket 1
Vacuum Booster:         Not included         Fuel Filter:         Not included         Priming Lever:         Not included         Maximum Static Pressure Above Outlet Height:         2.500 psi min to 4.000 psi maximum at 16 in. At 1800 rpm         Distance From Pump Mounting Face To Actuator Center:         1.749 in. To centerline of cam         Inlet Connection Type/size:         Fuel 0.125 in. Pipe size         Outlet Connection Type/size:         Fuel 0.125 in. Pipe size         Distance From Pump Mounting Face To Actuator Center:         1.749 in. To centerline of cam         Inlet Connection Type/size:         Fuel 0.125 in. Pipe size         Outlet Connection Type/size:         Fuel 0.125 in. Pipe size         Drain Facility:         Not included         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:         No         Fig:	Stroke Length:
Not included Fuel Filter: Not included Fuel Filter: Not included Priming Lever: Not included Maximum Static Pressure Above Outlet Height: 2.500 psi min to 4.000 psi maximum at 16 in. At 1800 rpm Distance From Pump Mounting Face To Actuator Center: 1.749 in. To centerline of cam Inlet Connection Type/size: Fuel 0.125 in. Pipe size Outlet Connection Type/size: Fuel 0.125 in. Pipe size Dutlet Connection Type/size: Fuel 0.125	0.312 inches
Fuel Filter:   Not included   Priming Lever:   Not included   Maximum Static Pressure Above Outlet Height:   2.500 psi min to 4.000 psi maximum at 16 in. At 1800 rpm   Distance From Pump Mounting Face To Actuator Center:   1.749 in. To centerline of cam   Inlet Connection Type/size:   Fuel 0.125 in. Pipe size   Outlet Connection Type/size:   Fuel 0.125 in. Pipe size   Drain Facility:   Not included   Shelf Life:   N/a   Unit Of Measure:       Demilitarization:   No   Fig:	Vacuum Booster:
Not included Priming Lever: Not included Maximum Static Pressure Above Outlet Height: 2.500 psi min to 4.000 psi maximum at 16 in. At 1800 rpm Distance From Pump Mounting Face To Actuator Center: 1.749 in. To centerline of cam Inlet Connection Type/size: Fuel 0.125 in. Pipe size Outlet Connection Type/size: Fuel 0.125 in. Pipe size Drain Facility: Not included Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not included
Priming Lever: Not included Maximum Static Pressure Above Outlet Height: 2.500 psi min to 4.000 psi maximum at 16 in. At 1800 rpm Distance From Pump Mounting Face To Actuator Center: 1.749 in. To centerline of cam Inlet Connection Type/size: Fuel 0.125 in. Pipe size Outlet Connection Type/size: Fuel 0.125 in. Pipe size Drain Facility: Not included Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Fuel Filter:
Not included Maximum Static Pressure Above Outlet Height: 2.500 psi min to 4.000 psi maximum at 16 in. At 1800 rpm Distance From Pump Mounting Face To Actuator Center: 1.749 in. To centerline of cam Inlet Connection Type/size: Fuel 0.125 in. Pipe size Outlet Connection Type/size: Fuel 0.125 in. Pipe size Drain Facility: Not included Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Not included
Maximum Static Pressure Above Outlet Height: 2.500 psi min to 4.000 psi maximum at 16 in. At 1800 rpm Distance From Pump Mounting Face To Actuator Center: 1.749 in. To centerline of cam 1.749 in. To centerline of cam Inlet Connection Type/size: Fuel 0.125 in. Pipe size Outlet Connection Type/size: Fuel 0.125 in. Pipe size Drain Facility: Not included Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Priming Lever:
2.500 psi min to 4.000 psi maximum at 16 in. At 1800 rpm Distance From Pump Mounting Face To Actuator Center: 1.749 in. To centerline of cam Inlet Connection Type/size: Fuel 0.125 in. Pipe size Outlet Connection Type/size: Fuel 0.125 in. Pipe size Drain Facility: Not included Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Not included
Distance From Pump Mounting Face To Actuator Center: 1.749 in. To centerline of cam Inlet Connection Type/size: Fuel 0.125 in. Pipe size Outlet Connection Type/size: Fuel 0.125 in. Pipe size Drain Facility: Not included Shelf Life: Iv/a Unit Of Measure: Demilitarization: No Fig:	Maximum Static Pressure Above Outlet Height:
1.749 in. To centerline of cam Inlet Connection Type/size: Fuel 0.125 in. Pipe size Outlet Connection Type/size: Fuel 0.125 in. Pipe size Drain Facility: Not included Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	2.500 psi min to 4.000 psi maximum at 16 in. At 1800 rpm
Inlet Connection Type/size: Fuel 0.125 in. Pipe size Outlet Connection Type/size: Fuel 0.125 in. Pipe size Drain Facility: Not included Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Distance From Pump Mounting Face To Actuator Center:
Fuel 0.125 in. Pipe size Outlet Connection Type/size: Fuel 0.125 in. Pipe size Drain Facility: Not included Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1.749 in. To centerline of cam
Outlet Connection Type/size:Fuel 0.125 in. Pipe sizeDrain Facility:Not includedShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	Inlet Connection Type/size:
Fuel 0.125 in. Pipe size Drain Facility: Not included Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Fuel 0.125 in. Pipe size
Drain Facility: Not included Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Outlet Connection Type/size:
Not included Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Fuel 0.125 in. Pipe size
Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Drain Facility:
N/a Unit Of Measure:  Demilitarization: No Filg:	Not included
Unit Of Measure:  Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
7400	Fiig:
I 109-b	Т109-b