NSN 2910-00-563-5495

Cam Actuated Fuel Pump - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2910-00-563-5495 **Mounting Type:** Nonstandard **Overall Length:** 5.156 inches **Overall Height:** 8.125 inches **Overall Width:** 4.062 inches **Actuation Method:** Direct cam **Fording Feature:** Not included **Furnished Items And Quantity:** Gasket 1 Stroke Length: 0.250 inches Vacuum Booster: Included **Vacuum Booster Location: Bottom** Minimum Vacuum In Rpm: 8.5 in. Mercury at 1200 rpm **Fuel Filter:** Not included **Priming Lever:** Included **Maximum Static Pressure Above Outlet Height:** 5.25 lb at 16 in. At 1800 rpm **Distance From Pump Mounting Face To Actuator Center:** 1.750 in. To centerline of cam **Inlet Connection Type/size:** Fuel 3/8-18 npsf thd, vacuum 1/8-27 npsf thd **Outlet Connection Type/size:** Fuel 3/8-18 npsf thd, vacuum 1/8-27 npsf thd **Drain Facility:** Not included Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 2910-00-563-5495

Cam Actuated Fuel Pump - Page 2 of 2



Fiig:

T109-b