NSN 2910-00-595-2771

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2910-00-595-2771

| Mounting Type: | | | | | |
|---|--|--|--|--|--|
| Bracket head | | | | | |
| Mounting Hole Diameter: | | | | | |
| 0.406 inches | | | | | |
| Mounting Hole Quantity: | | | | | |
| 2 | | | | | |
| Body Length: | | | | | |
| 6.313 inches | | | | | |
| Body Width: | | | | | |
| 5.000 inches | | | | | |
| Body Height: | | | | | |
| 3.438 inches | | | | | |
| Distance Between Mounting Hole Centers: | | | | | |
| 4.250 inches | | | | | |
| Design Type: | | | | | |
| Reusable | | | | | |
| Features Provided: | | | | | |
| Drain plug | | | | | |
| Bracket Quantity: | | | | | |
| 2 | | | | | |
| Filtering Element Quantity: | | | | | |
| 1 | | | | | |
| Maximum Operating Pressure: | | | | | |
| 4.0 pounds per square inch | | | | | |
| Filtering Media Design: | | | | | |
| Single stacked disks single filtering media response | | | | | |
| First Intake Connection Type: | | | | | |
| Threaded internal pipe side | | | | | |
| First Discharge Connection Relationship To Intake Connection: | | | | | |
| Identical to first intake connection | | | | | |
| First Intake Thread Series Designator: | | | | | |
| Npt | | | | | |
| First Intake Thread Size: | | | | | |
| 0.125 inches | | | | | |
| First Intake Thready Qty Per Inch (tpi): | | | | | |
| 27 | | | | | |
| First Intake Thread Direction: | | | | | |
| Right-hand | | | | | |
| Material: | | | | | |
| Iron cast sediment bowl | | | | | |
| Fsc Application Data: | | | | | |

Engine fuel system, nonairborne

NSN 2910-00-595-2771

Fluid Filter - Page 2 of 2



| _ | | | | |
|---|----|------|---|------|
| c | hο | JIF. | | ife: |
| J | | | _ | HG. |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000