NSN 2910-00-735-1345

Cam Actuated Fuel Pump - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2910-00-735-1345 **Mounting Type:** Nonstandard **Overall Length:** 5.000 inches **Overall Height:** 8.078 inches **Overall Width:** Between 3.969 inches and 4.031 inches **Actuation Method:** Direct cam **Fording Feature:** Not included **Furnished Items And Quantity:** Gasket 1 Stroke Length: 0.250 inches Vacuum Booster: Included **Vacuum Booster Location: Bottom** Minimum Vacuum In Rpm: 6 in. Mercury at 120 rpm **Fuel Filter:** Not included **Priming Lever:** Included **Maximum Static Pressure Above Outlet Height:** 5-1/4 lb at 16 in. At 1800 rpm **Distance From Pump Mounting Face To Actuator Center:** 1.750 in. To center of cam eccentricity **Inlet Connection Type/size:** Fuel 0.375 in.-18 thd size, vacuum 0.125 in.-27 in.-27 thd size **Outlet Connection Type/size:** Fuel 0.375 in.-18 thd size, vacuum 0.125 in.-27 thd size **Drain Facility:** Not included **Fsc Application Data:** Fuel system, engine, nonaircraft Shelf Life:

Unit Of Measure:

N/a

NSN 2910-00-735-1345

Cam Actuated Fuel Pump - Page 2 of 2



Demilitarization:

No

Fiig:

T109-b