Cam Actuated Fuel Pump - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2910-00-917-9721

| Mounting Type: |
|--|
| Sae alternate |
| Overall Length: |
| Between 5.340 inches and 5.400 inches |
| Overall Height: |
| Between 5.000 inches and 5.060 inches |
| Overall Width: |
| Between 3.090 inches and 3.150 inches |
| Actuation Method: |
| Direct cam |
| Fording Feature: |
| Not included |
| Furnished Items And Quantity: |
| Gasket 1 |
| Stroke Length: |
| 0.250 inches |
| Vacuum Booster: |
| Not included |
| Fuel Filter: |
| Included |
| Fuel Filter Location: |
| Side |
| Priming Lever: |
| Not included |
| Maximum Static Pressure Above Outlet Height: |
| 3.25 lb at 16 in. At 1800 rpm |
| Distance From Pump Mounting Face To Actuator Center: |
| 1.640 in. To center of cam eccentricity |
| Inlet Connection Type/size: |
| Fuel 0.125 in27 npsf thd size |
| Outlet Connection Type/size: |
| Fuel 0.125 in27 npsf thd size |
| Drain Facility: |
| Not included |
| Fsc Application Data: |
| Engine fuel system components, nonaircraft |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

No

NSN 2910-00-917-9721

Cam Actuated Fuel Pump - Page 2 of 2

Fiig: T109-b

